




MLB BREAST MILK REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Fan Forced System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Interior LED Lighting
- Automatic Condensate Water Disposal
- Fan Door Switch
- Data Logger included
- Battery Backup for Controller
- Digital Display with Built-in Alarms
- Hi/Lo Readout
- Self-closing Doors



	2°C to 4°C
	29 L 59 L 125 L 300 L
	445w x 458d x 535h 450w x 460d x 875h 595w x 610d x 840h 595w x 611d x 1560h

PH: (07) 3390 7011

EMAIL: admin@hoylandmedical.com.au

Hoyland Medical

Service and quality to the medical profession

MLB BREAST MILK REFRIGERATOR



MODEL	MLB29G	MLB59G	MLB125G	MLB300G*
Gross Capacity	29 L	59 L	125 L	300 L
External Dimensions in mm (w/d/h including castors or legs)	445 x 458 x 535	450 x 460 x 875	595 x 610 x 840	595 x 611 x 1560
Internal Dimensions in mm (w/d/h)	361 x 205 x 400	390 x 390 x 720	505 x 442 x 625	505 x 442 x 1345
Packed Dimensions in mm (w/d/h including pallet)	500 x 575 x 590	660 x 705 x 910	660 x 705 x 910	660 x 705 x 1630
Gross Weight – kg (packed weight)	30	41	59	77
Net Weight – kg	27	38	55	73
Voltage	240V			
Temperature Range	2°C to 4°C			
Ambient Temperature Range	10°C to 32°C			
Refrigerant	R600			
Cooling System / Defrost	Fan Forced / Automatic			
Exterior Cabinet Finish	Enamelled Steel			
Inner Liner Material	ABS			
Door	Glass			
Door Hinge	RH			
Door Handle	Pull Handle			
Type of Controller	Digital			
Temperature Display	External			
Data Logger	Included			
Door Ajar Alarms	Yes			
High and Low Readout	Visual / Audible			
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Yes Optional			
Port Entry	Yes			
Battery Back-Up for Controller	Yes			
Power Requirement	10 amp GPO			
Watts	125w			145w
Castors	No, Adjustable Levelling Legs			
Adjustable Shelves	Yes			
Usable Shelf Area in mm (w/d)	2 x 376 x 190	2 x 368 x 271 1 x 376 x 190	2 x 488 x 411 1 x 488 x 276	6 x 488 x 411 1 x 488 x 276
Light	LED			

*For low volume use only – No more than 25 openings per hour.
For high use needs please see NHRT.
Nuline Refrigeration reserves the right to alter the specifications without prior notice.