Miele

PW 6163 [EL WEK]

Hygiene washing machine, electrically heated Barrier machine for retirement and care homes as well as hospitals.



- Drum volume 160 l, load size 16.0 kg
- Wide variety of programmes special disinfection programme
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 46 %*, g-factor400
- * Residual moisture specification relates to a hot rinse during the last rinse cycle.

EAN: 4002516446569 / Material number: 11812720 / Old Material Number: 516163057ER

Old Material Number: 51616305ZER	
Construction type and version	
Construction type	Hygiene washing machine
Range	Professional
Front	Iron grey
Load ratio	1:10
Load in kg	16,0
Drum volume in I	160
Door opening [W] in mm clean side	352
Door opening [H] in mm clean side	366
Door opening [W] in mm unclean side	352
Door opening [H] in mm unclean side	366
Door opening angle in degrees	153
Maintenance-free motor with frequency converter	•
Stainless steel honeycomb drum	•
Application	
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for hospitals	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for hot water connection in I/kg	9,63
Specific energy consumption for hot water connection in kWh/kg	0,13
Programme duration in minutes with cold water connection	63
Programme duration in minutes with cold water and hot water connection	55
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	46
Spin speed in rpm	1025
g factor	400
Tested operating hours	30000
Control system	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard/target grp programmes	
Basic programmes	•
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for dry cleaners	•
·	



PW 6163 [EL WEK]

Hygiene washing machine, electrically heated
Barrier machine for retirement and care homes as well as hospitals.



EAN: 4002516446569 / Material number: 11812720 / Old Material Number: 51616305ZER	
Programmes for small businesses	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Programmes for hospitals	•
Programmes for beauty clinics, spas, and fitness studios	•
Dispensing	
Detergent drawer	4 compartments
Liquid dispensing module (optional)	•
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensor Standard electrical connection	
	Electric
Heating type Electrical connection	3N AC 400V 50/60HZ
	15,00
Heater rating in kW	-
Total connected load in kW	18,00
Fuse rating in A	25
Water connection/drainage	2x 1/2" hose w/ 3/4" th.
Cold water [number]	union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Hard water [number]	2 x 1/2" w/ 3/4" union
Dump valve	DN 70
Dimensions and weight	
External dimensions, height in mm	1718
External dimensions, width in mm	1153
External dimensions, depth in mm	1070
	1800
External dimensions, gross height in mm	
External dimensions, gross height in mm External dimensions, gross width in mm	1310
	•
External dimensions, gross width in mm	1310
External dimensions, gross width in mm External dimensions, gross depth in mm	1310 1138
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg	1310 1138 630,0
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg	1310 1138 630,0 648
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace	1310 1138 630,0 648
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data	1310 1138 630,0 648 7479
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace	1310 1138 630,0 648 7479 70 dB(A) re 20 µPa
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h	1310 1138 630,0 648 7479 70 dB(A) re 20 µPa
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features	1310 1138 630,0 648 7479 70 dB(A) re 20 µPa
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing Imbalance monitoring	1310 1138 630,0 648 7479 70 dB(A) re 20 µPa
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring	1310 1138 630,0 648 7479 70 dB(A) re 20 µPa
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing Imbalance monitoring	1310 1138 630,0 648 7479 70 dB(A) re 20 µPa
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring	1310 1138 630,0 648 7479 70 dB(A) re 20 µPa
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side	1310 1138 630,0 648 7479 70 dB(A) re 20 µPa 6,50 • • • •
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+	1310 1138 630,0 648 7479 70 dB(A) re 20 µPa 6,50 • • • • •
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element	1310 1138 630,0 648 7479 70 dB(A) re 20 µPa 6,50 • • • • • • • •
External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Maximum floor load in N Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Patented pre-spin Cloth reprocessing Imbalance monitoring Temperature monitoring Two indicator lights on the clean side Automatic drum positioning and locking Special heater element Automatic load control+	1310 1138 630,0 648 7479 70 dB(A) re 20 μPa 6,50 • • • • • • • • •



PW 6163 [EL WEK]

Hygiene washing machine, electrically heated Barrier machine for retirement and care homes as well as hospitals.



EAN: 4002516446569 / Material number: 11812720 / Old Material Number: 51616305ZER Emergency switch-off Machine-independent accessories Efficiency and sustainability 95 Recycling rate in % Connection options Optical interface for service access Serial interface module RS 232 (optional) Peak-load negotiation / energy management (optional) Operating data acquisition Water recovery (optional) Capacities Synthetic duvets [number] 2 Synthetic pillows [number] 4 2 Down duvets [number] 4 Down pillows [number] Cloths, 22 g [number] Cotton mops, 40 cm / 190 g [number] 84 Cotton mops, 50 cm / 220 g [number] 73 Microfibre mops, 40 cm / 120 g [number] 133 Microfibre mops, 50 cm / 170 g [number] 94 Standards, test certificates and symbols CE VDE-EMC VDE Splash-proof safety rating IPX4 UKCA WEEE Complies with Machinery Directive 2006/42/EC