



Rextorm PX-501

Gen II (PX-501B)

10.1" Fully Rugged Tablet





IP65

MIL-STD-810G





1000 nits

5-foot Drop

- IP65, MIL-STD-810G, 5-foot drop resistance
- 1000 nits sunlight readable display
- ◆ GNSS, Wi-Fi, Bluetooth and optional 4G LTE
- Capacitive touch supports digitizer, glove touch, digitizer by request
- Hot swappable battery design
- Wide expansion design for data capture
- Dual pass-through connector for WLAN, GNSS, WWAN



Specifications

System

- Intel® Core™ i5-5350U 1.8GHz
- 8GB DDR3L
- ♦ 128GB mSATA SSD, expandable to 256GB
- OS option : Windows 10 IoT Enterprise

Display

- 10.1" TFT LCD WUXGA (1920 x 1200), 1000 nits high brightness
- Capacitive multi-touch screen supports glove touch, water rejection, palm rejection, 2mm hard tip stylus
- Gorilla Glass; digitizer by request

Communication

- ◆ Gigabit Ethernet (RJ45)
- ♦ Wi-Fi 802.11 a/b/g/n/ac
- ♦ Bluetooth V4.0 + EDR
- ♦ GNSS (GPS/ GLONASS/ BeiDou)
- Optional 4G LTE

Camera

- 2MP front camera
- ♦ 8MP auto focus rear camera with LED flash

Control Button

- Programmable button x 3
- Barcode trigger x 1
- Power, volume, Windows button

Expansion Option

- Built-in 2D barcode reader
- NFC + Smart card reader 2-in-1 module
- Fingerprint reader, UHF RFID reader
- Snap-on connector easy for customization



For further information or pricing, please contact us:

Melbourne 03 9872 4592 Sydney 02 9460 4355 Brisbane 07 3868 4255 Adelaide 08 8343 8516

sales@metromatics.com.au www.metromatics.com.au

I/O Interface

- ♦ USB 3.0 type A x 1
- RS-232 x 1, option USB 2.0 type A
- ◆ Audio headset jack (Headphone/ microphone combo) x 1
- ◆ Micro SD slot x 1, Micro SIM slot x 1, Micro HDMI x 1
- RF pass-through connector for WLAN/ GNSS/ WWAN x 2
- ◆ Docking connector (12-pin) x 1
- DC-in x 1

Power

- AC adapter (65W, 100-240V AC, 50/60Hz)
- 4500mAh hot swappable battery, 6.5 hours battery life ¹
- Optional 9000mAh hot swappable battery, up to 13 hours battery life¹

Rugged Feature

- ◆ IP65 and MIL-STD-810G certified
- ♦ Vibration, shock and 5-foot drop resistance

Environmental

- ◆ Operating temperature : -20° C to +60° C
- ◆ Storage temperature : -30° C to +70° C
- Humidity: 95%, non-condensing

Dimensions & Weight

- ◆ 28 x 19.5 x 2.3 cm (11" x 7.7" x 0.9") (W x H x D)
- ◆ 1.36kg (3.0 lbs) II

Software

♦ DashON

Security

- ◆ TPM 2.0
- ◆ Phoenix SecureWipe by request

Accessories



Detachable Keyboard



VESA Bracket



Vehicle Dock



Hand Strap



Desktop Dock



Handle



Hard Handle



4-bay Battery Charger



Shoulder Strap



IP54 Digitizer Pen

See website for more accessories.



Listed battery life is based on MobileMark 2012® productivity mode testing with wireless on. Battery life rating is for comparison purposes only. Actual battery life varies by configuration, application, power management and operating conditions.

II. Actual weight varies by configurations and optional accessories.