

CONDENSING UNITS SEALED UNITS

Hermetic compressor, crankcase heater where provided.

Galvanized sheet metal base and copper tube air condenser. Aluminium fins with axial fans.

Liquid receiver with overpressure discharge device.

Liquid and suction taps in standard models for valve expansion.

In the water-cooled version, a fan is installed to cool the compressor.

For versions using R290 mini-channel capacitors and approved components are provided.

The units can be equipped with the following accessories:

- Liquid line
- Safety and control pressure switches
- Liquid and oil separator
- Power, gas and water pressure regulators
- Power electrical panel and condenser fan management
- Remote electronic instrumentation for monitoring or regulation



TN -5°C/-15°C

TECHNICAL DATA

V34.3/A 2V

Unit	Voltage	volt/f/Hz	220/240-1-50HZ	
	Absorption	W	1144	
		A	5,67	
	Compressor	model	NEK6217GK	
		cc	14	
	Coolant	R452A		
Expansion management	Exp. Valve			
Condensation	Cond. type	air		
Sizes	Liq. line diam.	mm	10	
	Suct. line diam.	mm	12	
	Height (H)	cm	650	
	Depth (P)	cm	480	
	Width (L)	cm	270	
	Weight	kg	35	
T	Max ambient temp.	°C	32	

SELECTION TABLE

TC -5°C	W	1375
TC -10°C	W	1151
TC -15°C	W	950