



# V6

Vital Signs Monitor



NEW

**General:**

**Size and Weight**

- Size: 160×130×260mm (W×H×D)
- Weight: (2.5 kg) (Including a lithium battery)

**Display**

- Type: 7" Color Anti-glare TFT LCD
- Resolution: 234×480 pixels

**Power supply**

- Input voltage: AC: 100V~240V, 50Hz/60Hz
- Input power: 70VA

**Battery**

- Type: 11.1V 4000mAh rechargeable lithium ion battery
- Operating time: >8 hours
- Charge time: 6h to 100% (Standby)

**Data Storage**

- Clinic Mode:
  - Patient quantity: 1000
  - Recording number: 16000
  - Single patient clinic record number: 1~16000
- Monitor Mode:
  - Patient quantity: 1
  - Trend data: resolution 1Min: can store 96 hours
  - resolution 5 Min: can store 480 hours
  - resolution 10 Min: can store 960 hours
- Alarm events: 1000
- NIBP measurement record: 5000

**Environmental Specifications**

- Operating
  - Temperature: (5~40) °C
  - Humidity : ≤85% (noncondensing)
  - Atmospheric Pressure: (700~1060) hPa
- Transportation and Storage
  - Temperature: (-20~+55)
  - Humidity : ≤93% (noncondensing)
  - Atmospheric Pressure: (500~1060) hPa

**PR**

- Measurement range: 20~250 bpm
- Resolution: 1 bpm
- Accuracy: ±1% or ± 1 bpm, whichever is the greater

**Performance:**

**BLT Digital SpO<sub>2</sub>**

- Measurement range (0~100) %
- Resolution: 1%
- Accuracy: ± 2% (70%~100%)
- ± 3% (35%~69%)
- unspecified (0~34%)

**Masimo SpO<sub>2</sub>(Option)**

- Measurement range: (0~100)%
- Resolution: 1%
- Accuracy: ±2% (70% to 100%) (adult/pediatric, non-motion conditions)
- ±3% (70% to 100%) (neonate, non-motion conditions)
- ±3% (70% to 100%) (motion conditions)
- Unspecified (0% to 69%)

**Nellcor SpO<sub>2</sub> (Option)**

- Measurement range: (0~100) %
- Resolution: 1%
- Accuracy: ± 2% (70%~100%) (adult)
- ± 3% (70%~100%) (neonate)
- ± 2% (70%~100%) (low perfusion)
- unspecified (0~69)%

**NIBP**

- Technique: Automaticoscillometry
- Range: Adult: 10~270mmHg
- Child: 10~235mmHg
- Neonate: 10~135mmHg
- Accuracy: Static ±3 mm Hg
- Clinic: Average error: ±5 mmHg
- standard deviation: ≤8 mmHg
- Unit: mmHg.kPa
- Pulse rate range: 40-240 bpm

**Microstream EtCO<sub>2</sub> (Option)**

- Measurement way: Infrared spectrum
- Measurement mode: sidestream
- Sample flow rate: 50 ml/min ± 10 ml/min
- Measurement range: (0~19.7) %, (0~150 mmHg)
- Resolution: 0.1% or 1mmHg
- Unit: %, mmHg, kPa
- Accuracy: ±2 mmHg 0 mmHg to 40 mmHg,
- ±5% of reading 41 mmHg to 70 mmHg,
- ±8% of reading 71 mmHg to 100 mmHg,
- ±10% of reading 101 mmHg to 150 mmHg,
- ( 760mmHg, temperature is 25 °C )
- (when RR >80 rpm, all the range is ±12% of reading)

**Standard Configuration**

NIBP, BLT digital SPO<sub>2</sub>, PR, Lithium Battery

**Option**

Masimo SpO<sub>2</sub>, Nellcor SpO<sub>2</sub>, Micro-Stream EtCO<sub>2</sub>, Instant infra-Red ear thermometer, Barcode Scanner, Touch Screen



\*Specifications subject to change without prior notice.