

M9

Z168.720



- For loads up to 3.000 kg.
- Versatile and compact.
- Pneumatic wheels.
- 5-levels speed adjustment.
- Wide range of accessories and connections.
- Optional remote control driving.
















Main sectors



WASTE HANDLING



HOSPITALS



FOOD INDUSTRY



INDUSTRIAL MAINTENANCE



PRODUCTION LINES



AIRPORTS




INTEGRATED LOGISTICS & RETAIL CHAINS

Performances on slopes

While the force expressed in N at the hook remains unchanged, the following circumstances **may affect the towing** capacity expressed in kg:

- type of ground on which the towing is performed;
- towing on flat ground or on a slope;
- use (or not) of ballasts;
- type of wheels mounted on the vehicle and on the trailer.







5 levels speed adjustment

On the new M9 tillerhead by Zallys a button for the adjustment of the speed of the machine is mounted as standard. By clicking it, at each click you switch to the next level. This allows a fast and easy selection of the correct speed based on the kind of maneuvre. The Flex-to-Go system has been studied to give a better maneuverability in confined spaces and more speed on the longer journeys.

Each click adds 20% more speed.

Speed ramp:

20% - 40% - 60% - 80% - 100%

Once the maximum speed is reached, by pressing the button again it returns to 20%.





Ergonomic driving

Zallys' tillerhead has been conceived and produced to make the use of the machine more ergonomic for the operator, guaranteeing the right comfort while driving during the work shift. Its ergonomic design allows to have all the driving controls at your fingertips, the display with the battery charge level and the power key for an easy and fast ignition. The structure is made of resistant materials in case of accidental bumps.







Pneumatic wheels

M9 is equipped with **pneumatic wheels**, suitable both for indoor and outdoor use, always guaranteeing the maximum grip and a really low level of vibrations. Moreover, they are very resistant and offer exceptional performances on every kind of ground. The traction axis is located on the rear of the machine to offer a better stability and more control over the direction of the trailer to be towed.



Autonomy for a full workday

M9 is powered by two 105/130 Ah batteries, which guarantee the machine for 8 hours operation at continuous use. In case of a particularly intense use, it is possible to equip higher amperage batteries, or equip an interchangeable and extractable battery pack, for a 24 / 7 operation. In both cases they are easy and safe to recharge, thanks to the high frequency external battery pack.



Modular ballast system

Zallys modular system guarantees **maximum flexibility** on increasing the vehicle's performances. With just **8,5 kg unit weight**, single ballasts are lightweight and can be equipped **without physical effort by the operator**, while maintaining all their effectiveness.

STANDARD HITCH





















STANDARD HITCH

A more efficient way to manage carts




M9 can be configured for the driving mode with **remote control**. With this option, the machine becomes the perfect solution for handling trains of carts: the operator can control the direction of the carts while driving the machine from a distance. M9 with remote control lets one single operator to handle up to 60 shopping carts at the same time, for an average of 350 carts per hous (to obtain the same results without using the machine it would be necessary to employ 4 operators). Moreover, thanks to our **modular hitch**, maximum compatibility is guaranteed with most of the carts on the market.



ACCESSORIES











Examples of applications

on various production sectors



METALLURGICAL INDUSTRY







INDUSTRIAL MAINTENANCE









SUPERMARKETS & LARGE DISTRIBUTION











Zallys srl srl - Via Palazzina 1, Sarcedo 36030 (VI) - Italia

Contacts:

sales@zallys.com +39 0445 366785

Web site:

www.zallys.com



