# SJE MICROMASTER®, SJE MICROMASTER® PLUS, SJE MICROMASTER® SPDT PUMP FLOATS

### Mechanically-activated, wide-angle switch designed for performance and dependability.

These mechanically-activated, wide-angle switches provide automatic control of pumps in:

- Water
- Sewage applications

These pump switches are not sensitive to rotation or turbulence allowing them to be used in both calm and turbulent applications.

Hydraulic

### **SPECIFICATIONS**

- Flexible SJOW, water-resistant (CPE) cable
- High impact, corrosion resistant, polypropylene float housing
- Temperature rating up to 60° C (140° F)
- Maximum water depth of 9 meters (30 feet) or 90 kPa (13 psi)
- IPX8 enclosure rating
- Float dimensions: 7.0 cm diameter x 12.3 cm long (2.74 inch x 4.83 inch)
- Suitable for Category II installations
- · Protected by double insulation
- Adjustable pumping range of 20 to 91 cm (8 to 36 inches)
- CE Certified units available by request

**NOTE:** These switches are not recommended for controlling electrical loads less than 100 mA, 12 VAC. Must be used with pumps that provide integral thermal overload protection.


### **MODEL SPECIFIC SPECIFICATIONS**

SJE MICROMASTER® pump float		
Voltage 50 Hz/60 Hz Single Phase	Maximum Pump Running Current	Maximum Pump Starting Current
125/250 VAC	10 amps	60 amps
Cable:	18 gauge, 2 conductor	

SJE MICROMASTER® Plus pump float		
Voltage 50 Hz/60 Hz Single Phase	Maximum Pump Running Current	Maximum Pump Starting Current
125/250 VAC	12 amps	60 amps
Cable:	16 gauge, 2	conductor


SJE MICROMASTER® SPDT pump float		
Voltage 50 Hz/60 Hz Single Phase	Maximum Pump Running Current	Maximum Pump Starting Current
125/250 VAC	10 amps	60 amps
Cable:	18 gauge, 3 conductor	


Can be wired to operate in either pump down (normally open) or pump up (normally closed) applications. Single Pole, Double Throw




Pump Up is normally closed contacts for filling.

**SJE MicroMaster® SPDT** pump switch has 3 conductors for pump down and pump up operation.









## SJE MICROMASTER®, SJE MICROMASTER® PLUS, SJE MICROMASTER® SPDT PUMP FLOATS

### **OPTIONS**

Bagged Packaging is standard.

**Piggy-Back Plug** - North American standard plug. Options are available for SJE MicroMaster® and SJE MicroMaster® Plus pump switches. Please contact the factory.

CE Certified units available upon request.

### **MicroMaster Ordering Information**

RBS Sto	ck Code	Description
P/Up	P/Down	
3710350	3710365	Micromaster, 3mtr, 2-Wire, No Plug
3710355	3710370	Micromaster, 5mtr, 2-Wire, No Plug
3710360	3710375	Micromaster, 10mtr, 2-Wire, No Plug
	3710380	Micromaster, 20mtr, 2-Wire, No Plug
	3710383	Micromaster, 50mtr, 2-Wire, No Plug

3710371	Micromaster, 5mtr, With Plug*
3710376	Micromaster, 10mtr, With Plug*

<sup>\*</sup> Fitted with pigyback plug. Allows you to plug in the pump directly, no further wiring required.

### **MicroMaster SPDT Ordering Information**

RBS Stock Code	Description
3710385	MicroMaster SPDT, 3-wire, 5mtr, No Plug
3710390	MicroMaster SPDT, 3-wire, 10mtr, No Plug
3710391	MicroMaster SPDT, 3-wire, 20mtr, No Plug
3710392	MicroMaster SPDT, 3-wire, 30mtr, No Plug
3710393	MicroMaster SPDT, 3-wire, 50mtr, No Plug

### **Accessories**

3710499	Cable Weight 800g
---------	-------------------



9500192E 07/20 © 2018 SJE, Inc. All Rights Reserved. SJE RHOMBUS is a trademark of SJE, Inc.