GH6000E



GH6000E



PORTABLE POWER



Technical

Model Туре Speed Phase/Voltage Frequency Max Output @ 0.8pf Noise Level (dBA @ 7m) Frame

GH 6000F Portable 3000 RPM 1/240 50 Hz 6.0kVA 72 Extra Large Roll Frame

Engine

Manufacturer **Engine Model** Туре Start Fuel Run Time Tank Capacity HP 3000 rpm cont **Cubic Capacity Oil Capacity**

Honda GX390 O.H.V. Electric Start **Unleaded Petrol** 2.6 hr @ 100%, 3.8hrs @60% 6.1 L 8.0 HP 389 Cm3 1.1 L

Alternator

Alternator Brand Туре Harmonic Distortion **Protection Class Insulation Class**

Meccalte **Brushless** Less than 5% IP 23 Class H

10amp + 15amp switched with thermal overload

Dimensions & Weight 85 Cm Length Width 57 Cm

Width	57 011	
Height	60 Cm	
Weight	75 Kg	

Options

Outlets

Outlet

Outlets Protection Wheel kits Frames Alternators Long Range Tank

Standard (thermal overload protected), RCD + Weatherproof Outlets (IP66 rated) RCD/ELCB IP30 or IP66 Two wheel or four wheel Extra Large Roll Frames Oversized, Single or Three Phase 15 Litre Capacity

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.