

SCG80S3

Silent Type

Powered By Cummins



CONFIGURATION:

Standard: Engine, alternator, cooling system, Base frame, shock absorber, air system, control box, plastic fan blades (when the engine and water tank do not bring).


Optional: Water jacket heater, oil preheater, anti-condensation heater, fuel water separator, fuel heater, fuel level sensor, water level sensor, automatic fueling system (only supporting base frame including fuel tank).

Accessories: Silencer, bellow, exhaust silencing system accessories (with the matching engine), regular battery, data of generators, random tool (with the matching engine).

FETURES

- >> Powered by Cummins engine with reliable power output
- >> Easy maintenance and operation
- >> High durability of maximum performance
- >> With forklift pockets and lift point for transportation
- >> Suitable for all weather conditions

Basic Information



Engine		Cummins 4BTA3.9-G11
Alternator		Stamford UCI224G
Controller		Smartgen HGM6120
Prime Power	KVA/KW	80/64
Standby Power	KVA/KW	88/70.4
Rated Speed	RPM	1500
Rated Frequency	HZ	50
Rated Voltage	V	415/240
Phase		3
Power Factor		0.8
Governer method		Mechanical
Rated Current	A	111.3
Fuel Consumption @ 100% Load	L/H	18
Dimension	LxWxH mm	2890*1100*1850
Dry Weight	Kg	1800
Fuel Tank Size	L	350
Noise Level @ 7 meters	dBA	72

Note:

- (1) **Prime Power:** Prime power is available for an unlimited number of annual operating hours in variable load applications; in accordance with ISO8528-1. A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation, in accordance with ISO3046-1.
- (2) **Standby Power:** Standby power is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.
- (3) The following voltages can be customized on requirement: single phase - 220V/230V/240V; three phase - 380/220V, 400/230V, 415/240V, 440/254V.
- (4) Pitmaster reserves the right to modify the specifications without prior notice. All ratings are for guidance only, please refer to the final specific generator information from Pitmaster.

SCG80S3

Silent Type

Powered By Cummins

Engine Specification

Model	4BTA3.9-G11
Manufacturer	Cummins
Number of cylinders	4
Cylinder arrangement	In-line
Cycle	Four stroke
Induction system	Turbocharged
Compression ratio	17.3:1
Bore x Stroke	102x120 mm
Displacement L	3.9
Estimated total weight (dry) kg	350
Rated power at 1500rpm KW/HP	70/93
Lubrication oil capacity L	10.9
Coolant capacity L	20.8
Governor method	Mechanical
Starting system	Electric
Type of injection model	BYC PB/Electronic Governor
110% Fuel Consumption (prime) L/H	20
100% Fuel Consumption (prime) L/H	17.6
75% Fuel Consumption (prime) L/H	13.2
50% Fuel Consumption (prime) L/H	9.1
Silence Type	Industrial
Lube Oil brand	15W40-CH4 Upgrade
Cooling System	Water cooled

Alternator Specification

Model	UCI224G
Frequency and Speed	50Hz/1500rpm
Manufacturer	Stamford
Prime capacity(kVA)	85
Exciter type	Brushless
Insulation	Class H
Protection	IP23
Rated power factor	0.8
Stator winding	Double layer concentric
Winding pitch	two thirds
Winding leads	12
Maximum over speed	2250Rev/min
THF (Wave Form IEC)	<2%
TIF (Wave Form NEMA)	<50
Voltage regulation	1.00%