



## QDD25P

Electric Tractor 2.5t

## Electric tractor 2.5t QDD25P

Distinguishing mark				
1.1	Manufacturer		EP	
1.2	Model designation		QDD25P	
1.3	Drive unit		Electrical	
1.4	Operator type		Standing	
1.5	rated capacity	Q	kg	450
	Rated drawbar pull		kg	2000
1.9	Wheelbase	y	mm	1055
Weight				
2.1	Service weight (include battery)		kg	750
2.2	Axle loading, laden Driving/loading		kg	640/560
2.3	Axle loading, unladen Driving/loading		kg	450/300
Types, Chassis				
3.1	Tyre type driving wheels/Loading wheels			solid rubber
3.2	Tyre size, driving wheels (diameter*width)		mm	4.00-8
3.3	Tyre size, steering wheels (diameter*width)		mm	15x4.5
3.5	Wheels, number driving/loading (x=drive wheels)		mm	1/2x
3.7	Track width, rear, loading side	b <sub>11</sub>	mm	664
Dimensions				
4.7	Height of overhead, No ladder	h <sub>6</sub>	mm	1265
	Height of overhead, Ladder with 3 stairs		mm	1940
	Height of overhead, Ladder with 5 stairs		mm	2480
4.12	Tow coupling height	h <sub>10</sub>	mm	320
4.13	Loading height, unladen	h <sub>11</sub>	mm	590
4.16	Length of loading surface	l <sub>3</sub>	mm	1300
4.18	Width of loading surface	b <sub>9</sub>	mm	740
4.19	Overall length, No ladder	l <sub>1</sub>	mm	2190
	Overall length, Ladder with 3 stairs		mm	2300
	Overall length, Ladder with 5 stairs		mm	2400
4.21	Overall width	b <sub>1</sub> / b <sub>2</sub>	mm	780
4.32	Ground clearance, center of wheelbase	m <sub>2</sub>	mm	74
4.35	turning radius	Wa	mm	1385
Performance data				
5.1	Travel speed, laden/ unladen		km/ h	7/7
5.5	Drawbar pull, laden/unladen		N	640
5.6	Max. drawbar pull, laden/unladen		N	2500
5.8	Max. gradeability, laden/unladen		%	5/20
5.10.1	Service brake type			hydraulic+Mechanical
5.10.2	Park brake type			hydraulic+Mechanical
Electric-engine				
6.1	Drive motor rating S2 60 min		kW	3
6.3	The maximum allowed size battery		mm	/
6.4	Battery voltage/nominal capacity K5			48/200
6.5	Battery weight		kg	200
Addition data				
8.4	Sound pressure level at the driver's ear		dB (A)	70
8.5	Traction pin type		dB (A)	Bolt type

- 1.The parameters in the table are of the standard model. For more information, please contact us.
- 2.The parameters are subject to change without notice.

