

TITAN LED ROTATING BEACON



TITAN LED ROTATING BEACON

HARDWIRE PART NO.	MAGNETIC PART NO.	COLOUR	CURRENT DRAW @12v	OPERATING VOLTAGE
LR3024AB	LR3024ABM	Amber	1.8 Amps	12-24 VDC
LR3024BB	LR3024BBM	Blue	1.8 Amps	12-24 VDC
LR3024CB	LR3024CBM	Clear	1.8 Amps	12-24 VDC
LR3024GB	LR3024GBM	Green	1.8 Amps	12-24 VDC
LR3024RB	LR3024RBM	Red	1.8 Amps	12-24 VDC
LR3024MB	LR3024MBM	Magenta	1.8 Amps	12-24 VDC



HALOGEN ROTATING BEACON

HARDWIRE PART NO.	MAGNETIC PART NO.	COLOUR	CURRENT DRAW @12v	OPERATING VOLTAGE
RHU312AB-12V	RHU312ABM-12V	Amber	4.8 Amps	12 VDC
RHU312AB-24V	RHU312ABM-24V	Amber	2.4 Amps	24 VDC
RHU312BB-12V	RHU312BBM-12V	Blue	4.8 Amps	12 VDC
RHU312BB-24V	RHU312BBM-24V	Blue	2.4 Amps	24 VDC
RHU312CB-12V	RHU312CBM-12V	Clear	4.8 Amps	12 VDC
RHU312CB-24V	RHU312CBM-24V	Clear	2.4 Amps	24 VDC
RHU312GB-12V	RHU312GBM-12V	Green	4.8 Amps	12 VDC
RHU312GB-24V	RHU312GBM-24V	Green	2.4 Amps	24 VDC
RHU312RB-12V	RHU312RBM-12V	Red	4.8 Amps	12 VDC
RHU312RB-24V	RHU312RBM-24V	Red	2.4 Amps	24 VDC
RHU312MB-12V	RHU312MBM-12V	Magenta	4.8 Amps	12 VDC
RHU312MB-24V	RHU312MBM-24V	Magenta	2.4 Amps	24 VDC



LENS
3124RL



LENS
3124AL



LENS
3124GL



LENS
3124CL



LENS
3124BL



LENS
3124ML



POLE MOUNT
3000PM



MAGNETIC KIT
3000M-KIT



GLOBE
H1 12V 55W
H1 24V 70W

DESCRIPTION

- LED: Aluminium base
- Hardwire Dimensions: H141mm x D161mm
- Magnetic Dimensions: H151mm x D161mm
- Low profile heavy duty beacon
- LED: CE and SAE Class 1 Certified
- Direct Silicone Drive for quieter operation
- Polycarbonate UV stabilised lens
- Aluminium base efficiently dissipates heat
- EMC/EMI Certified



PROGRESS BEYOND DEVELOPMENT