### Skid-Steer Loaders / A770 Skid-Steer Loader

# **Specifications & Options**

Standard	Optional	N/A Not Applicable	Units	US

#### **Bobcat A770**

### **Engine**

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	92 hp

### **Performance**

Rated Operating Capacity (SAE)	3,325 lb
Tipping Load	6650 lb
Operating Weight	9623 lb
Travel Speed	7.1 mph
Travel Speed (2-speed option)	12.3 mph

# **Capacities**

Fuel Tank	23.9 gal

# **Hydraulic System**

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23 gal/min
Auxiliary High Flow	36.6 gal/min

### **Dimension**

Length	141.6 in
Length without Attachment	114.3 in
Length with Standard Bucket	141.6 in
Width	74.7 in
Width (with bucket)	74 in
Height	81.3 in
Height with Operator Cab	81.3 in
Height to Bucket Hinge Pin	132 in
Reach @ Maximum Height	31.5 in
Turning Radius	85.8 in
Wheelbase	48.3 in
Turning Radius (AWS Mode)	151.5 in

#### **Features**

Joystick Control	
Air Conditioning	
Adjustable Seat	
Backup Alarm	
BICS System (Interlock)	
Cab Enclosure	
Sound Option	<b>☑</b>
Cab Heater	•
Operating Lights	
Rear Window	•
Heater Air Conditioning	
Top Window	•
Seat Belt	•
Suspension Seat	•
Two Speed Travel	•
Deluxe Instrumentation	✓
Engine Shutdown	•
Hydraulic Bucket Positioning	✓
High Flow Option	
Auxiliary Hydraulics	•
Spark Arrestor Muffler	•
Bob-Tach Attachment System	•
Power Bob-Tach	•
Ride Control	<b>▽</b>
Horn	

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.