



Specifications – General

- **Certification:** CCC, CE, FCC, ISO9001, BIS
- **Cooling System:** Fan cooling
- **Display Sizes:** 21.5", 23.6", 27", 32", 43", 50", 55", 65"
- **Enclosure Front Bezel:** Aluminum
- **Back Housing:** Cold-rolled steel plate
- **Mounting:** Default wall-mounting bracket
- **OS Support:** Microsoft® Windows 11/10 (64-bit)
 - Default: Windows 10/11 English Professional Trial Version
- **Optional Colors:** Silver, Black, White

Specifications – Physical

- **Weight (Net):** Pending
- **Weight (Gross):** Pending
- **Package Size:** Pending

System Hardware

- **CPU:** Intel® Core® i3 / i5 / i7
- **Memory:** 8GB / 16GB / 32GB DDR4
- **Storage:** 128GB / 256GB / 512GB / 1TB / 2TB SSD
- **Expansion Slots:** Full-size Mini PCI-E
- **LAN:** 100 Base-T x 1

I/O Ports

- **Power:** x 1
- **HDMI:** x 1
- **VGA:** x 1
- **USB:** x 4
- **LAN (RJ-45):** x 1
- **Audio Input:** x 1
- **Audio Output:** x 1
- **Other:** Customized interface available

Features

- **IPS LCD Sizes:** 21.5", 23.6", 27", 32", 43", 50", 55", 65"
 - 50K lifetime LED backlight
- **Operating System:** Android 11.0 with RK3566 / RK3568 / RK3588 processors
 - Memory up to 8GB ROM and 128GB RAM
- **Processor Options:** Intel® Core® i3 / i5 / i7 (latest generation)
 - Memory up to 32GB DDR4 SDRAM, 1TB SSD
- **Wide Operating Temperature:** -10°C ~ 50°C
- **Front Panel Protection:** IP65 certified
- **Touch Screen:** 10-point capacitive G+G

LCD Display

- **Display Type:** IPS LCD screen
- **Display Size:** Pending
- **Resolution:** 1920 x 1080 / 3840 x 2160
- **Max Colors:** 16.7M
- **Luminance:** 450 cd/m²
- **Viewing Angle (H/V):** 178° / 178°
- **Backlight Life:** 50,000 hrs
- **Contrast Ratio:** 3000:1
- **Aspect Ratio:** 16:9
- **Touch Lifespan:** 36 million touches at single point
- **Touch Type:** 10-point capacitive G+G touch screen
- **Response Time:** ≤ 5 ms

Environment

- **Humidity:** 10~95% RH @ 40°C, non-condensing
- **Ingress Protection:** Front panel IP65
- **Operating Temperature:** -10°C ~ 50°C
- **Storage Temperature:** -30°C ~ 70°C

Accessories

- **Adaptor (DC 12~19V)** with 1m cable
- **Power plug** with 1.2m cable
- **K-type bracket**


10 POINT SENSITIVE TOUCH

Sensitive multiple touch, Support multiple gestures, Easy to reach



SUPPORT MULTIPLE INFORMATION CHECKING SYSTEM

Floor guide, System management, Information query, Traffic query, etc.



REMOTE OPERATION

