



JUNIOR MAGICPILOT BUILT-IN

MKN No.: SKE623R_BI_G2




MKN combi steamer junior 6 tray, Gastronorm 2/3 with MagicPilot operation system and integrated steam condensation Hood (Built In Model)

Product Advantages:

- **Built In Model** – Integrated Steam Condensation Hood.
- **MagicPilot** – Robust, wear-free, capacitive true colour touch screen.
- **Video assist** – Interactive user assistance with clips featuring professional chefs.
- **CombiDoctor** – Self-diagnosis programme.
- Hygienic rounded corners and cooking chamber door with insulated **triple glazing**.
- **RackControl** – Multi-timer.
- **GreenInside** – Indicates the energy and water consumption for each cooking programme.
- **AutoChef** – Up to 350 individual cooking programmes and manual operating system.
- USB interface.2
- High speed centrifugal steam generation technology with heat recovery.
- **ClimaSelect** – Humidity and temperature control measurement.
- **WaveClean** – Automatic cleaning system (safe, easy, economical).
- **3 years warranty parts and labour.**

Installation requirements:

- Soft Water / Water supply / Connection to waste water provided by customer.
- If mineral content is high, reverse osmosis system may be advisable.



Technical Data:

Width x Height x Depth (mm)	550 x 799 x 611
Connected load (electrical) (kW):	5.2 or 3.5
Voltage (V) / EC:	415 3 phase AC or 240 1 phase AC
Recommended fuses (A):	3 x 20 or 1 x 15
Frequency range (Hz):	50
Soft Water connection:	DN 20 (R ¾" inside)
Water connection:	DN 20 (R ¾" inside)
Waterpressure (kPa):	200 - 600 (2 - 6 bar)
Drain connection:	DN 40
Gastronorm 2/3 (354 x 325 mm):	6 (max. 60 mm deep)
Plates Ø 28 cm:	6
Material housing:	1.4301
Material cooking chamber:	1.4301
Net weight (kg):	57
Heat emission latent (W):	936 / 630
Heat emission sensitive (W):	624 / 420
Type of protection:	IPX 5

