



GS360-LS

HORIZONTAL DIRECTIONAL DRILL

Robust and high-capacity, the GS360-LS delivers 5200 kN of thrust for demanding large-scale HDD applications. Built for power and precision, it offers exceptional torque and thrust in a heavy-duty frame—perfect for infrastructure, pipeline, and long-distance utility projects.

PRODUCT SPECIFICATIONS

OPERATION

	METRIC	IMPERIAL
Max Thrust & Pullback Force	380 kN	85,000 lbs
Max Thrust & Pullback Speed	36 m/min	118 ft/min
Max Torque	14,000 N.m	10,325 ft-lbs
Max Rotational Speed	135 r/min	
Walking Speed	2.5+ km/hr	1.6+ mph

DIMENSIONS

	METRIC	IMPERIAL
Length	7,300 mm	287 in
Width	2,230 mm	88 in
Height	2,310 mm	91 in
Weight	9,800 kg	21,600 lbs
Entry Angle	13-23 degrees	
Angle of Approach	18 degrees	

JB Trenchless supplies Goodeng HDD rigs and mud systems across Australia and New Zealand, backed by fast lead times, local support, and trusted service.

POWER

	METRIC	IMPERIAL
Engine	Cummins	
Engine Power	153 kW	205 HP
Fuel	Diesel	

FLUID SYSTEM

	METRIC	IMPERIAL
Max Mud Flow	400 L/min	105 gal/min
Max Mud Pressure	8 Mpa	1,160 psi

FEATURES

Rod Basket Capacity	~108m (4x9=36pcs Rods)
Breakout System	Standard hydraulic vice
Flow indicator	Standard meterage
Stakedown System	Hydraulic lever operated
Strike Alert	Standard
Remote Lockout	Standard
Seat Sensor	Standard



WWW.JBTRENCHLESS.COM



(03) 9706 5239



SALES@JBTRENCHLESS.COM