



<23.3 km Range per Charge



C 134.7 cm Turning Radius



Here to Push the Limits!

The Baja[™] Bandit is the outdoor mobility scooter you've been waiting for. Venture with confidence knowing you're equipped with the perfect blend of power and agility for all your journeys. This compact 10 km/h scooter is designed for various terrains thanks to its superior suspension and innovative braking system. Powered by a lightweight lithium battery for extended range, the Baja[™] Bandit is your ticket to adventurous off-road exploration.







Front, Rear & Seat Post Suspension





Front & Rear Bumper Guard

RANGE PER CHARGE (MAX) ^{1,3}	Up to 23.3 km
MAXIMUM WEIGHT CAPACITY	181 kg
TURNING RADIUS ²	134.7 cm
MAXIMUM SPEED ¹	10 km/h
LENGTH & WIDTH ^{2,5}	L: 126 cm W: 56 cm
SEAT TYPE DEPTH & WIDTH (STANDARD)	Foldable, compact, black vinyl D: 44 cm (17.3″) W: 46.5 cm (18.3″)
SEAT-TO-DECK HEIGHT	46 cm
SEAT-TO-GROUND HEIGHT ²	66 cm
GROUND CLEARANCE ²	4 cm at motor skid plate

OVERALL WEIGHT (NOT INC BATTERY) ⁴	72.3 kg
WEIGHT OF HEAVIEST PIECE ²	31.8 kg (front section)
SUSPENSION	Front, rear and seat post
3W/4W OPTION	4W
FRONT TYRES ²	9" solid
REAR TYRES ²	9" solid
BATTERY REQUIREMENTS	20Ah, 36V Lithium Ion battery
BATTERY CHARGER	Off-board, 4A Lithium charger
BATTERY WEIGHT ²	9.5 kg
COLOUR OPTIONS	Sage Tan

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%. Special order seats or non-standard dimensions will not fold-flat and depth-adjustable.

Continued Systems Continued Sy

1.	Varies with user weight, terrain type, battery
	amp hour (AH), battery charge, battery condition and tyre
	condition. This specification can be subject to a variance of 10%.
-	

- Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of 3%.
- Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from the theoretical calculations based on battery specification and drive system performance. Test conducted at maximum weight capacity.
- 4. Includes standard seat weight.
- 5. Width of base (does not include seat).

