

Titan Max-L19

Pneumatic Steel Strapping
Tool – Titan Max – L19

#61808



Lightweight

**Tubeless
Design**

**Comfortable &
User-friendly**

**Powerful
Tension**

The Titan Max - L19 is the optimal choice for those valuing low weight without compromising on strength and resilience. Weighing just 7kg, it ensures robustness and endurance in industrial settings. With its pneumatic technology and tubeless design, MAX-L19 guarantees reliable performance in daily strapping operations. MAX-L19 delivers a tension force of up to 5,500 N and accommodates strap thicknesses of up to 19 x 0.80 mm, making it a compact yet high-performing tool.

Features

- Tubeless Design: Simplifies handling
- Ergonomic design - ensures comfort and ease of use
- Powerful Tension: Up to 5,500 N (Adjustable)

Specifications

| | |
|--|--|
| Drive (tensioning) | Pneumatic |
| Tension Force | Max. 5,500 N (adjustable) |
| Drive (sealing) | Pneumatic |
| Seal Size | 19mm |
| Strap Feeding Speed | 10.97 cm/s |
| Dimensions | 381 mm x 170.18 mm x 269.24 mm (L x W x H) |
| Weight | 7.3 kg |
| Air Pressure | min. 6 bar flow pressure max. 7 bar back-pressure |
| Air consumption (during tensioning) | 5 litres per sec |
| Air consumption (during sealing) | 5 litres per sec |
| Cross-section | G 6.35mm |
| Noise level | 76 dB (A) |
| Strap Type | Steel |
| Strap Width | 19mm |
| Strap Thickness | 0.6 - 0.7mm |
| Seal Type | Seal-joint (double notch) |
| Sealing Strength | Up to approx. 75% of the strap breaking load |

