

# Machine Trailer

Professional and solid machine trailer with closed sides and 130 cm rear ramp



[ Model shown 3518 M4 ]

## MAXI-LOAD Machine trailer



Machine trailer with leaf springs

The powerful suspension is built up with Axles with parabolic leaf springs. The large brake drums with built-in closed bearings ensure stability and good braking performance.

The traction brake has an automatic reverse lock. This ensures easy coupling and disconnection of the trailer. All models are fully welded with a hot-galvanized chassis, beams, draw-bars and rear ramps.

The enclosed sides in galvanized steel plate and the heavy-duty wheel fender are standard.

The whole series is well thought out and well equipped.



Platform, spare wheel and jockey wheel are standard.



Powerful wheel fender in aluminum. Robust, non-slip and smooth.

VARIANT

## MAXI-LOAD Machine Trailer

For heavy daily use



See universal equipment on pages 38-39. Parts shown below are extra accessories.



Length 260 cm

**2015 M2**  
Inside box size: 260 x 150 x 30 cm  
Exterior box size: 268 x 158 x 38 cm  
Overall dimensions: 438 x 284 x 173 cm  
Gross weight: 2,000 kg  
Payload: 1,400 kg  
Wheel size: 13"  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 48 cm  
Ramp angle: 17°  
Also available with gross weight from 2,000 kg to 1,500 kg



Length 260 cm

**2715 M2**  
Inside box size: 268 x 150 x 30 cm  
Exterior box size: 268 x 158 x 38 cm  
Overall dimensions: 438 x 284 x 173 cm  
Gross weight: 2,700 kg  
Payload: 2,140 kg  
Wheel size: 13"  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 48 cm  
Ramp angle: 17°  
Also available with gross weight from 2,700 kg to 1,500 kg



Length 300 cm

**2718 M3**  
Inside box size: 308 x 188 x 30 cm  
Exterior box size: 308 x 188 x 38 cm  
Overall dimensions: 498 x 232 x 172 cm  
Gross weight: 2,700 kg  
Payload: 1,870 kg  
Wheel size: 13"  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 48 cm  
Ramp angle: 17°  
Also available with gross weight from 2,700 kg to 1,500 kg



Length 300 cm

**3518 M3**  
Inside box size: 308 x 188 x 30 cm  
Exterior box size: 308 x 188 x 38 cm  
Overall dimensions: 498 x 232 x 170 cm  
Gross weight: 3,500 kg  
Payload: 2,730 kg  
Wheel size: 12" Compact  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 38 cm  
Ramp angle: 17°  
Also available with gross weight from 3,500 kg to 2,700 kg



Length 400 cm

**2718 M4**  
Inside box size: 408 x 188 x 30 cm  
Exterior box size: 408 x 188 x 38 cm  
Overall dimensions: 597 x 234 x 168 cm  
Gross weight: 2,700 kg  
Payload: 1,893 kg  
Wheel size: 13"  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 48 cm  
Ramp angle: 17°  
Also available with gross weight from 2,700 kg to 1,500 kg



Length 400 cm

**3518 M4**  
Inside box size: 408 x 188 x 30 cm  
Exterior box size: 408 x 188 x 38 cm  
Overall dimensions: 608 x 234 x 168 cm  
Gross weight: 3,500 kg  
Payload: 2,693 kg  
Wheel size: 12" Compact  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 38 cm  
Ramp angle: 17°  
Also available with gross weight from 3,500 kg to 2,700 kg



Length 450 cm

**3520 M5**  
Inside box size: 458 x 188 x 29 cm  
Exterior box size: 458 x 206 x 30 cm  
Overall dimensions: 660 x 253 x 168 cm  
Gross weight: 3,500 kg  
Payload: 2,499 kg  
Wheel size: 12" Compact  
Axles: 3 axles, with brakes  
Side material: Steel  
Loading height: 38 cm  
Ramp angle: 17°  
Also available with gross weight from 3,500 kg to 2,700 kg

## Machine Trailer

With parabolic leaf springs ensuring strength and high comfort



[ Model shown 3518 M4 ]

## Almost all accessories are standard!



The construction machine trailer series is well equipped as standard. Developed by artisans and contractors who use it every day. The sturdy rear ramp has a built-in shock absorber for easy handling and adjustable drop-stands. This ensures stability in use. Ramp height 130 cm.

In addition, a heavily welded support rest (e.g. for the shovel or similar) and a spare wheel integrated underneath - can be found in front of the loading area. Non-slip pedestals are available on the sides and robust aluminum fenders make getting on and off easy and effortless. A very robust and powerful support wheel as well as internal and external lashing eyes complete the trailer.

Models with a gross weight of 3,500 kg have integrated locks in the ball head coupling.

The entire series is also available with 13" off-road wheels.

A lot of extra accessories are offered that make the trailer even more versatile.

VARIANT

## MAXI-LOAD Machine Trailer

Standard and extra accessories

Standard accessories



Parabolic leaf springs ensure high comfort and strength.



Platform and spare wheel, is standard on all models.



Aluminum wheel fender. Solid and strong. Completes the great exterior.



Shock absorber on ramp for easy handling, as well as adjustable stands.



Powerful jockey wheel, 3,500 kg extra strong. Coupling w/lock on 3,500 kg models.



Non-slip pedestals all around and external lashing eyes.



Solid and strong frame, fully welded and galvanized. High utility value!



Lashing eyes inside, attached at exterior frame for high strength.

EXTRA ACCESSORIES



Increases the life of your trailer and provides safe and non-slip up and down of stock.



13" with rough pattern for woods and construction site. Available for models with a gross weight of 3,500 kg.



Powerful toolbox with built-in lock for storage of straps etc.



Recessed lashing eyes in the floor. Also offered for aluminum floor.



Beautiful and bright LED light. Good security in the dark.

See universal equipment on pages 38-39. Parts shown below are extra accessories.



[www.variant-trailers.com.au](http://www.variant-trailers.com.au)



(02) 4367 0026



[info@variant-trailers.com.au](mailto:info@variant-trailers.com.au)

# Beavertail

"Maxi-Load" machine trailer with extra low drive



3516 B3  
with a  
payload of  
2.907 kg

[ Model shown 3516 B3 ]



[ Model shown 3516 B4 ]

## VARIANT

### MAXI-LOAD Beavertail

With extra high payload



13" with rough pattern for forest and building sites, for 3.500 kg models.



Recessed lashing eyes in the floor. Also offered for aluminum floor.

See universal equipment on pages 38-39. Parts shown below are extra accessories.



2716 B3 NEW

Inside box size: 386 x 162 x 23 cm  
Exterior box size: 386 x 168 x 23 cm  
Overall dimensions: 479 x 208 x 150 cm  
Gross weight: 2.700 kg  
Payload adjustable ramp: 2.172 kg  
Payload with full ramp: 2.171 kg  
Wheel size: 12" Compact  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 33 cm  
Ramp angle: 19°  
Also available with gross weight from 2.700 kg to 1.600 kg



3516 B3 NEW

Inside box size: 386 x 162 x 23 cm  
Exterior box size: 386 x 168 x 23 cm  
Overall dimensions: 482 x 208 x 150 cm  
Gross weight: 3.500 kg  
Payload adjustable ramp: 2.807 kg  
Payload with full ramp: 2.872 kg  
Wheel size: 12" Compact  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 33 cm  
Ramp angle: 22°  
Also available with gross weight from 3.500 kg to 2.700 kg



2718 B4

Inside box size: 488 x 180 x 30 cm  
Exterior box size: 488 x 186 x 30 cm  
Overall dimensions: 587 x 234 x 168 cm  
Gross weight: 2.700 kg  
Payload adjustable ramp: 1.945 kg  
Payload with full ramp: 1.915 kg  
Wheel size: 12" Compact  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 31 cm  
Ramp angle: 13°  
Also available with gross weight from 2.700 kg to 1.600 kg



3518 B4

Inside box size: 488 x 180 x 30 cm  
Exterior box size: 488 x 186 x 30 cm  
Overall dimensions: 608 x 234 x 168 cm  
Gross weight: 3.500 kg  
Payload adjustable ramp: 2.715 kg  
Payload with full ramp: 2.885 kg  
Wheel size: 12" Compact  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 29 cm  
Ramp angle: 12°  
Also available with gross weight from 3.500 kg to 2.700 kg



Parabolic leaf springs ensure high comfort and strength.



Platform and spare wheel, is standard on all models.



Aluminum wheel fender. Solid and strong. Completes the great exterior.



Powerful jockey wheel, 3.500 kg extra strong. Coupling w/lock on 3.500 kg models.

## Beavertail

"Maxi-Load" machine trailer with extra low drive



The strong construction of the machine trailers, here with the angled rear (Beavertail), makes the trailers particularly suitable for transporting machines and lifts with exceptionally low ground clearance.

With a loading height down to 29 cm, all driveways can be easily handled, whether they are scissor lift, belt excavator or similar.

All models are part of the Maxi-Load program. This means strong leaf springs as well as fully welded and hot-galvanized chassis.

By default, the trailers have 2 slides.

It allows for rear-facing overhang, and custom weight distribution.

All models can be supplied with a full rear ramp for a supplement.

Dropstands on both ramp types ensure stable support during loading and unloading.

Ramp length on B3 models is 118 cm and on B4 models 130 cm.

Non-slip pedestals all around, lashing eyes, platform and nose wheels are also standard accessories.

The B4 models are also equipped with spare wheels, mounted under the platform.

Spare wheels can be purchased for B3 models as additional equipment.

To further strengthen the trailer, whole aluminum floor can be purchased.

For both models with a gross weight of 3.500 kg, 13" terrain wheels with rough pattern can be purchased.

## EXTRA ACCESSORIES - full rear ramp



Complete rear ramp for easy rear overhang adjustment.



The aluminum floor shown is extra equipment.

## Machine Tipper

Hot-dip galvanized, robust and multifunctional

## VARIANT

### Machine and Tipping trailer

2 in one!



[ Model shown 3515 MT ]



Electric hydraulic tipping with built-in battery, charger and remote control with cable. Wireless control via app and smartphone can be purchased (factory assembly only)

## Machine Tipper

Machine trailer and tipper trailer, all in one!



Highly developed trailer series with all the features of the machine trailer and the tipping trailer:

Electric hydraulic tip which is perfect for unloading sand, stone, rubble, etc., as well as a low loading height for machinery and equipment.

All of this is combined in this specially designed "Machine Tipper", as with the low loading height, is particularly suitable for transporting mini excavators.

At the same time it can manage unloading of items with a single push on the remote control.

Features that previously required two different trailers.

The strong basic thoughts in this trailer series must be found in the thoroughly tested machine trailers and 3-way tippers from the Variants Maxi-Load series. We simply have taken the best of both types.

The machine tipper series is built on a fully welded and hot galvanized chassis,

which is equipped with leaf springs and brakes from one of Europe's leading manufacturers.

All of this helps to ensure high strength and good handling.

Standard accessories include the electric hydraulic with built-in battery and charger, powerful jockey wheel, top hinged and detachable rear bumper, ramp drawers under the bar, and 6 powerful inner lashing eyes. The electric-hydraulic system can be switched off with the main switch key.

## Lots of extras

Driving ramps for use of driving on machines.

Smooth steel base for easy and effortless unloading of sand, stones and rubble.

Wireless tip is offered by factory mounting of the smart Icarus system.

Strong quality dropstands mounted under the load.

LED lights for bright lighting.

See universal equipment on pages 38-39. Parts shown below are extra accessories.



3015 MT

Inside box size: 300 x 150 x 30 cm  
Exterior box size: 300 x 156 x 30 cm  
Overall dimensions: 426 x 186 x 95 cm  
Gross weight: 3.000 kg  
Payload: 2.500 kg  
Wheel size: 12" Compact  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 45 cm  
Tipping angle: 50°  
Ramp angle: 12°  
Also available with gross weight from 3.000 kg to 1.600 kg



3515 MT

Inside box size: 300 x 150 x 30 cm  
Exterior box size: 300 x 156 x 30 cm  
Overall dimensions: 426 x 186 x 95 cm  
Gross weight: 3.500 kg  
Payload: 2.823 kg  
Wheel size: 12" Compact  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 45 cm  
Tipping angle: 50°  
Ramp angle: 12°  
Also available with gross weight from 3.500 kg to 2.700 kg



3517 MT NEW

Inside box size: 300 x 170 x 30 cm  
Exterior box size: 306 x 176 x 30 cm  
Overall dimensions: 503 x 215 x 94 cm  
Gross weight: 3.500 kg  
Payload: 2.556 kg  
Wheel size: 12" Compact  
Axles: 2 axles, with brakes  
Side material: Steel  
Loading height: 45 cm  
Tipping angle: 48°  
Ramp angle: 12°  
Also available with gross weight from 3.500 kg to 2.700 kg



Parabolic leaf springs ensure high comfort and strength.



Aluminum wheel fender. Solid and strong. Completes the great exterior.



Jockey wheel. With ribs on 3.500 kg models. Coupling with lock on 3.500 kg models.



Lockable ramp drawers. Ramps can be purchased.

## EXTRA ACCESSORIES




Platform and spare wheel, is extra accessories.



With opening in front and rear. Height 80 cm.




Smooth, for easy unloading of gravel, etc. - protects the veneer floor.



Powerful model - mounted under the loading area.



For the use of machines in the driveway. The specially developed aluminum ramps have a particularly high level of quality and ensure even access to the trailer. The ramps are stored in an integrated screened shaft during a journey.



Beautiful and bright LED light. Good security in the dark.



Powerful toolbox with built-in lock, for storage of straps etc.