



Polar — PO 8T

Catering 8 x 1/1 Tray Capacity



Technical data

| Gross volume | 291 lt |
|---------------------------------|------------------------|
| Working temperature | -40+10 °C |
| Performance from +90°C to +3°C | 28 Kg |
| Performance from +90°C to -18°C | 22 Kg |
| Motor type | Plug-in |
| Refrigerant | R452A |
| Refrigeration power | 3289 W (-10°C / +40°C) |
| Absorption | 2052 W |
| Voltage/Frequency | 230V/1~/50Hz |

Refrigeration details

| Refrigeration unit | Tropicalized condensing unit. Equipped with thermostatic valve. Con-denser is oversized to ensure maximum efficiency and performance |
|------------------------|---|
| Refrigerant charge | 1800 gr |
| Evaporator | Conceived to provide the maximum exchange surface and to ensure optimal performance. Equipped with cataphoresis anti-corrosion treatment and door that can be opened for an easy cleaning |
| Defrost | Manual by air. The equipment can work for 24 hours avoiding ice formation on the evaporator |
| Condensate evaporation | Through easy extractable condensation collector tray (for installations without water drain system) |







Construction details

| Product dimensions WxDxH | 800x825x1435 |
|----------------------------|--|
| Packaging dimensions WxDxH | 870x900x1570 |
| Gross weight | 155 Kg |
| Structure | Stainless steel AISI 304 monocoque |
| External/Internal material | Inside and outside in stainless steel AISI 304; motor unit compartment and bottom in colaminated steel |
| Insulation thickness | 60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP) |
| Door | 1 Self-closing door right hinged, not reversible on site |
| Door gasket | Magnetic and removable, designed to improve insulation and to reduce energy consumption |
| Feet | AISI 304 stainless steel, height adjustable (135mm-230mm) |
| | |

Functions

| Control panel | Capacitive, simple and intuitive display |
|-----------------|--|
| Open door alarm | Visual and acoustic |
| Functions | Soft and hard blast chilling, soft and hard blast freezing, automatic end cycle holding, pre-cooling |
| Probe | Needle probe with automatic recognition of the probe inserted in the food |
| | |

Accessories

| No. included accessories | 8 - Pair of runners for GN 1/1 and EN 600x400 mm |
|--------------------------|--|
| | |

Versions

| Versions | Water cooling unit/ Power supply frequency 60Hz |
|----------|---|
|----------|---|

Technical data sheet ENPolar PO 8T Catering

Updated on 06-04-2022

