

GH7000EH



PORTABLE POWER

Technical

Model GH 7000EH – 'Hire Spec'

Type Portable
Speed 3000 RPM
Phase/Voltage 1/240
Frequency 50 Hz
Max power kW 7.0kW
Continuous Output 8.0kVA
Noise Level (dBA @ 7m) 72

Frame Extra Large roll frame

Engine

ManufacturerHondaEngine ModelGX390TypeO.H.V.

Starting Recoil & Electric start
Fuel Unleaded Petrol

Run Time 2.6 hr @ 100%, 3.8hrs @60%

Tank Capacity6.1 LHP 3000 rpm cont8.0 HPCubic Capacity389 Cm3Oil Capacity1.1 L

Alternator

Alternator Brand Meccalte
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23

Protection Class IP 23
Insulation Class Class H

Outlets

Outlet IP66 Rated 10amp + 15amp switched with Earth Leakage Circuit Breakers & RCD

Dimensions & Weight

 Length
 85 Cm

 Width
 57 Cm

 Height
 60 Cm

 Weight
 80 Kg

Options

Wheel kits Two wheel or four wheel Frames Extra large Roll Frames

Alternators Oversized, Single or Three Phase

Long Range Tank 15 Litre Capacity

