



TECHNICAL INFORMATION

Dimensions	735w x 750d x 2225h
Rack Dimension	500 x 500
Clear Entry Height	440
Rinse Water Consumption	2.2L Per Cycle

WATER CONNECTIONS

Connection Point	3/4 inch (19mm)
Inlet Temperature	20c Max
Flow Rate	4 L/Min
Flow Pressure	1.5 bar/Min
Wastewater Connection	23.6mm

ELECTRICAL

3 Phase (Standard)	415v 3P 50Hz - 20amp (TCL 9.7Kw)
3 Phase (Optional)	415v 3P 50Hz - 25amp (TCL 11.5Kw)
3 Phase (Optional)	415v 3P 50Hz - 32amp (TCL 15.7Kw)

GENERAL DATA

Weight (Net/Gross)	163/187Kg
Tank Capacity	35L
Noise Emission	62dB(A)
Cycle Times	80/110/140 Seconds (Adjustable)

STANDARD INCLUSIONS

1x 3phase Lead
1x 1m Flexible Water Connection Hose
1x 1m Flexible Waste Hose
2x 500 x 500 Racks (1x Flat, 1x Plate)

OPTIONS

Automatic Hood: Automatic opening and closing of the hood by press of a button
Driven Rinse System to reduce the rinse water volume

STANDARD FEATURES

- Smart touch display: simple single button operation
- Top & bottom S shaped washfields
- Variopower washing pressure adjustment
- Chemical pumps
- Rinse booster pump
- Drain pump
- Active energy management
- EnergyLight: waste water heat recovery system
- Quadruple filtration
- Clouding sensor
- Connected wash
- Timer for automatic start up and close down
- Hood start: washing program starts by closing the hood
- Exhaust air heat recovery: reduces steam and energy costs

CERTIFICATES

WRAS
Watermark Approval
Hygiene Certificate according to DIN 10534