

KBS 400 DG NA FULLY-AUTOMATIC, DOUBLE COLUMN MITRE BAND SAW



ADVANTAGES AT A GLANCE:

- Vertical saw in robust twin-column construction
- ▶ Single, layer and bundle cuts
- Excellent band life and the best cutting quality due to an inclined sawband
- High cutting performance due to a powerful drive motor
- NC-controlled cutting angle setting
- Machine operation via graphical user interface with touch screen
- Sawband drive/Sawband feed (strong drive power for increased cutting speed; infinitely-variable sawband feed can be adjusted directly on the saw frame; long sawband life even with the most varied material dimensions)
- NC-controlled cutting angle setting (adjustment of freestanding control console; automatic, hydraulic clamping of the machine after reachig the mitre setting)
- Material feed gripper (feed gripper with hydraulic clamping unit; positioning drive with servo motor and planetary gearing over precision measuring rack and absolute rotary encoder; minimal remnant lenghts due to optimized gripper contour)





HARD FACTS

- Sawband: 5.730 x 34 x 1,1 mm
- Drive performance: 3,0 kW
- ► Cutting speed: 15 90 m/min
- ▶ Feed rate: 0 300 mm/min
- Fast return stroke: 2.500 mm/min
- Machine weight: 3.600 kg
- Machine dimensions: (L x W x H): 2.710 x 4.520 x 2.150 mm
- Working range
 - ■□ Square material 400 x 350 mm
- ▶ Stroke length single stroke: 2.600 mm
- Mitre range: -45°/90°/+30°
- Tools: Bi-Metal

APPLICATIONS

Steel fabrication, steel service center, automotive sector, agriculture, machine construction, etc.