

8.5kg TOP-LOAD WASHERS



MAT20



DEEP-WATER WASH SYSTEM

- Provides optimal wash performance with deep-water wash and rinse cycle options and vigorous cleaning action
- Traditional flex-vane agitator provides four distinct wash profiles — from aggressive to gentle — designed to pull clothes from the top to the bottom of the wash basket
- PowerWash® cycle provides more agitation, hotter water, and an extra rinse for the dirtiest loads



TRADITIONAL FLEX-VANE AGITATOR

- Powered by a ½ hp PSC motor with “fin” design
- Alternates between four distinct wash patterns — from aggressive to gentle
- Generates outstanding clothes movement and extensive deep-cleaning action to tackle a variety of loads



CONTROLS TO MEET YOUR NEEDS

- Mechanical controls provide a simple user interface with robust, easy-to-use knobs (MAT20CS and MAT20MN)
- Get flexibility and individual cycle pricing options for optimal earnings through Intelligent Controls with M-Series Technology, while end users can easily choose their preferred wash experience with one-touch cycle selection (MAT20PD)



CARD READER COMPATIBLE

- Order your new washer as Card Only to prevent vandalism and increase safety on site.
- Never have to worry about where the gold coins from your laundry end up with real time reporting and payment deposited straight into your nominated bank account.
- Card Reader accepts Visa, Mastercard, Paywave, Paypass, Apple Pay and Android Pay.



BUILT TO LAST

- Heavy-duty front panel — robust and easy to remove
- Front-panel accessibility — provides fast entry to the motor, transmission, and wash tub for streamlined self-service
- Built-in, easy-to-use diagnostics — help servicers identify problems quickly
- Watertight, flexible, triple-lip seal — helps keep moisture safely away from the shaft and protects the premium bearings



COIN DROP/CARD READER READY
MAT20PD (pictured)



COIN SLIDE
MAT20CS (pictured)



NON-COIN
MAT20MN (pictured)

8.5kg Top-Load Washer Models	
Payment Configuration	Model Number
Coin Drop or Card Reader Ready	MAT20PD
Coin Slide	MAT20CS
Non-Coin, Push to Start	MAT20MN




See maytagcommerciallaundry.com for warranty details.

8.5kg TOP-LOAD WASHERS




MAT20



FRONT VIEW



SIDE VIEW



BACK VIEW



*Includes height of metercase.

**Based on 2018 United States DOE J2 Testing with factory preset cycles.

Dimensions are for planning purposes only. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

Printed on Recycled Paper.

MODELS	MAT20PD	MAT20CS	MAT20MN
Payment Configuration	Coin Drop or Card Reader Ready	Coin Slide	Non-Coin
DIMENSIONS			
Depth — mm	660	660	660
Width — mm	686	686	686
Height — mm	1,130*	1,130*	1,130*
Lid Opening — mm	432	432	432
CRATED DIMENSIONS			
Crated Width — mm	737	737	737
Crated Depth — mm	699	699	699
Crated Height — mm	1,255	1,255	1,255
APPROXIMATE WEIGHT			
Uncrated — kg	72.1	70.8	65.8
Crated — kg	80.3	78.9	73.9
ELECTRICAL REQUIREMENTS			
Voltage	220-240V - 50Hz	220-240V - 50Hz	220-240V - 50Hz
Breaker/Fuse — Amps	10	10	10
WATER INLET HOSE/DRAIN HOSE			
Operating Pressure — psi (Bar)	20–100 (1-8)	20–100 (1-8)	20–100 (1-8)
Inlet Hose Length — m	1.8	1.8	1.8
Drain Hose Length — m	1.3	1.3	1.3
APPROXIMATE WATER USAGE			
Average Total Water Usage Per Cycle — litres	62.8**	93.3**	93.3**
Average Hot Water Usage Warm Water Cycle — litres	2.1	2	2
Average Hot Water Usage Hot Water Cycle — litres	26.6	24.6	24.6
Extract Speed — Max G-Force/Max RPM	144 / 700	144 / 700	144 / 700
Motor Size — hp (kW)	1/2 (.37)	1/2 (.37)	1/2 (.37)



Maytag Commercial Install Summary



MAT20 Top Load Washer

- Standard 10AMP GPO within 1.0m to plug into
- ¾" hot and cold water taps within 1m
- Standpipe or laundry drain minimum 77cm high

Before operation:

- Installation manual to be read
- Unit to be levelled



MHN33 Front Load Washer

- Standard 10AMP GPO within 1.0m to plug into
- ¾" hot and cold water taps within 1m
- Standpipe or laundry drain minimum 77cm high – if supplied on plinth, laundry drain to be 102cm high

Before operation:

- Installation manual to be read
- Shipping bolts to be removed
- Power cord to be pulled through
- Unit to be levelled

MDE20 or MDE28 ELECTRIC Dryer.

- No power cord supplied - requires hardwiring into a dedicated 1 phase 25AMP circuit by your electrician.
- Requires fluing to external air using single skin 100mm rigid galv²

*Natural gas as standard - LPG Conversion Kits available.

Before operation:

- Installation manual to be read
- Unit to be levelled

MDG20 or MDG28 GAS Dryer.

- Standard 10AMP GPO within 1.0m to plug into
- Licensed gas plumber required to connect to gas and fluing on site
- Requires fluing to external air using single skin 100mm rigid galv²

*Natural gas as standard - LPG Conversion Kits available.

Before operation:

- Installation manual to be read
- Unit to be levelled

Install summary is a brief guide only and does not cover all requirements.

Full installation manual is supplied with each machine as hard copy and is also available via email on request.

1 – Clearances are minimum for dryer free air requirements. Additional clearances may be required depending on fluing and supply requirements on site.

2 - All dryers must be flued to external air with rigid galvanised ducting. Dryers in outdoor areas require fluing to direct heat and lint away from unit. Multiple /group dryer ducting requirements as per installation manual.

Ducting available from Dependable Laundry Solutions.



Maytag Commercial Install Summary

MLE22PN/PD ELECTRIC Stack Washer/Dryer

- No power cord supplied - requires hardwiring into a dedicated 1 phase 25AMP circuit by your electrician.
- ¾" hot and cold water taps within 1m
- Standpipe or laundry drain minimal 77cm high
- Minimum 110mm clearance behind unit¹
- Requires fluing to external air using single skin 100mm rigid galv²

Before operation:

- Installation manual to be read
- Shipping bolts to be removed
- Unit to be levelled
- Service key is bubble wrapped in machine drum – needs to be stored & kept



MLG22PN/PD GAS Stack Washer/Dryer

- Standard 10AMP GPO within 1.0m to plug into
- ¾" hot and cold water taps within 1m
- Standpipe or laundry drain minimal 77cm high
- Minimum 110mm clearance behind unit¹
- Requires fluing to external air using single skin 100mm rigid galv²
- Licensed gas plumber to connect to gas and fluing

*Natural gas as standard - LPG Conversion Kits available.

Before operation:

- Installation manual to be read
- Shipping bolts to be removed
- Power cord to be pulled through
- Unit to be levelled
- Service key is bubble wrapped in machine drum – needs to be stored & kept.

MLE27PN/PD ELECTRIC Stack Dryer/Dryer

- No power cord supplied - requires hardwiring into a dedicated 1 phase 50AMP circuit by your electrician.
- Minimum 110mm clearance behind unit¹
- Requires 2 x fluing to external air using single skin 100mm rigid galv²

Before operation:

- Installation manual to be read
- Unit to be levelled
- Service key is bubble wrapped in machine drum – needs to be stored & kept

MLG27PN/PD GAS Stack Dryer/Dryer

- Standard 10AMP GPO within 1.0m to plug into
- Minimum 110mm clearance behind unit¹
- Requires 2 x fluing to external air using single skin 100mm rigid galv²
- Licensed gas plumber to connect to gas and fluing

*Natural gas as standard - LPG Conversion Kits available.

Before operation:

- Installation manual to be read
- Unit to be levelled
- Service key is bubble wrapped in machine drum – needs to be stored & kept

