

Beever 2021 SINGLE



HEAVY-DUTY INDUSTRIAL WOOD CHIPPERS FROM THE INDUSTRY LEADER

1300 072 926 | globalmachinerysales.com.au

VIC 24-28 Williams Road Dandenong Sth. 3175

E sales@globalmachinerysales.com.au **F** (03) 9791 7676

NSW Unit 1/21 Penny Place Arndell Park 2148 **E** sales@globalmachinerysales.com.au

F (02) 8678 2478

MORBARK BEEVER 2021 AXLE

BENEFITS



- With its large capacity and high-production volume reduction capabilities, this chipper is perfect for residential tree services, vegetation management, lot and land clearing, maintenance contractors and municipalities.
- The 2021 boasts a huge list of options to customize the machine as well as more standard features than any other chipper in its class.
- The unit can be outfitted with a four- or six-cylinder diesel engine and choice of single axle, tandem axle or single axle dual wheel package.
- The dual-sided, chambered air impeller system with controllable air flow vents increases chip-throwing velocity and easy discharge of light, leafy material.
- Like all Morbark equipment, the 2021 is a long-lasting, durable machine backed by a world-class parts and service support team.



TorqMax[™] Feed Wheel

The TorqMax[™] dual feed wheel compression system provides more than 11,161 kg/m of material pulling force.



Infeed

The 165cm wide x 96.5cm high infeed chute with 78.7cm wide x 52cm high throat opening allows for easy feeding of a variety of materials.



Reversing Auto-Feed

The reversing auto-feed system automatically stops forward feed and briefly backs material away from the drum for optimum performance.



Hydraulic Down Pressure

The Variable Force™ Hydraulic Down Pressure System eliminates the use of springs and creates up to 4,536 kgs of perpetual down pressure.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

General

Chipping capacity	20" (50.8cm)
Engine	
Horsepower	215 HP
Height	
Width	231.1 cm
Length	645.16
Weight	4,990 kgs
Suspension	Heavy Duty leafspring
Infeed opening	65" wide x 38" high
Throat opening	
Drum23.5	
Fuel/hydraulic capacity	227/155 litres
Frame	5 cm x 15.2 cm tubular
Brakes	Air brakes
Tyres	235/75Rx17 ½"
Hitch	63.5 mm Pintle Ring

Equipment Highlights

60cm wide x 95cm diametre, four dual-edged knife staggered-pocket drum with patented EZ Drum removable knife holders, dual-sided, chambered air impeller system and controllable air flow vents.

Dual horizontal feed wheels with TorqMax top feed wheel compression system, hydraulic lift assist and Variable Force constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle.

Live hydraulic system including: ball valve, pump, motor, and valve bank with additional preplumbed valve section for installation of an aftermarket winch package.

Hydraulic 360° chute with manual heightadjustable discharge.

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection.

Options Include

ChipSafe® Operator Safety Shield
Folding infeed tray with spring lift assist
Winch package: heavy-duty, 2,268 kgs pull
capacity with rope and 305 cm chafe guard
Bottom Bump Bar
Hydraulic Swivel Discharge
Cone Holder
Spare Tyre/Mount
Folding Infeed Tray
Flow Control
Axle Options Available
Fender Options Available
Battery Box Options Available
Custom paint and logo packages



