



17" Medical Grade All-In-One Computer/Tablet

Slim, Antimicrobial, ANSI/AAMI ES60601-1 Certified Tablet for Efficient Operations

The 373T/MD All-In-One computer/tablet features the integration of a brilliant 17" capacitive touch screen and a high performance, energy-efficient Intel® Core™ i processor within a slim, durable package. With built-in front and back cameras, Wi-Fi as well as optional data capture modules, this medical AIO computer/tablet offers health professionals an effective tool to monitor, record and retrieve patient information. With its large, vivid display, the 373T/MD shows a wide work area and detailed application interface to enhance user experience and workflow.

Features

- 17" Full-HD capacitive touch screen, digital pen support
- Intel® Core™ i processor
- Microsoft® Windows® 10/11 IoT Enterprise operating system
- NIST compliant BIOS available
- ANSI/AAMI ES60601-1 certified with antimicrobial enclosure
- IP65-rated front panel
- Hot-Swappable battery pack
- Built-in front and back cameras
- VESA plate compatible for mounting

Major Options

- Smart card/CAC reader
- 4G LTE/AWS

System	373T/MD
CPU	Intel® Core™ i5-1135G7, 4-Core, 4.2 GHz, Intel® Core™ i7-1165G7, 4-Core, 4.7 GHz
RAM	8GB to 16GB
Storage	256GB to 1TB Flash
Operating System	Microsoft® Windows® 10/11 IoT Enterprise
NIST Compliance	NIST Compliant BIOS Available
Display	17" LED-Backlit Touchscreen
Display Resolution	1920 x 1080
WLAN	Wi-Fi 802.11ax, 2.4GHz/ 5GHz dual band
Control Switch and Buttons	1 x Power Button, 3 x Programmable Buttons
Microphone & Speaker	Built-In Microphone and Speaker
Camera	Full-HD Front Camera & 8 MP Back Camera
I/O Ports	
USB Port	6 x USB 3.0, 1 x USB Type C
Headset Jack	1 (3.5 mm)
Ethernet Port	1 (RJ45)
DC-in	1
Mechanical and Environmental	
AC/DC Adapter	Input: 100-240V AC; Output: 18.5V DC, 3.89A
Battery Pack	Hot-Swappable Battery (11.4V, 5400mAh)
Enclosure	ABS + PC Plastics and Magnesium-Aluminum Alloy with Antimicrobial Enclosure
Dimensions (H x W x D)	430 X 282 X 27mm
Weight	2 kg
VESA-compliant Mounting	75mm x 75mm VESA standard
Durability	IP65-Rated Front Panel
Regulatory	FCC/IC, CE/CB, RCM, ANSI/AAMI ES60601-1
Temperature	Operation: -10°C to 60°C, Optional -30°C to 60°C Storage: -55°C to 70°C
Humidity	0% - 90% non-condensing
Major Options Specs	
Smart card/CAC reader	Full-Slot (Reads ISO 7816 T=0, T=1); 1.8/3/5V Smart Card
Mobile Broadband	4G LTE/AWS

HPAWM17V122