

Paxum® X1000mp

Paxum Fully Automatic Pallet Wrapping Machine - Rotary Arm

#62216



25-30 Pallets
per Hour

Noiseless
Operation

Intelligent
Technology

Advanced
Safety Measures

Introducing the X1000mp Paxum model a Fully Automatic Pallet Wrapping Machine. Designed for industrial applications, this cutting-edge machine offers exceptional efficiency and performance for your packaging needs. With advanced features and reliable technology, it is the ultimate solution to optimize your pallet wrapping process.

Highlights

Enhanced flexibility:

- Direct placement of pallets on the floor
- No requirement for a loading ramp for pallet placement
- No weight restrictions for loading
- Reduced installation space needed

Robust wrapping arm:

- The X1000mp utilizes a slewing bearing drive
- The rotary arm operates durably, quietly, and requires no future maintenance.

Advanced Wrapping Safety Measures:

In case of any contact between the arm and objects during the wrapping process, the entire machine will instantly stop, ensuring high-level safety.

Smart Operating System and PCB Control System:

- The machine is equipped with an operation guide solution that provides step-by-step instructions on how to operate it.
- In case of any issues with the machine, the screen displays solutions to guide you in resolving the problem promptly.
- The PCB control system makes maintenance easier and more convenient.



Robust Wrapping Arm



Advanced Safety Measures

Features

- Impressive wrapping speed: 25-30 pallets per hour
- Auto film cutting and clamping
- Automatic top sheet dispenser (optional)
- Automatic paper corner fixer (optional)
- SEW & SIEMENS motor drive system
- Advanced photoelectric sensor
- Noiseless operation
- Maximum pre-stretch rate of up to 400%



Smart Operating System and PCB Control System

Specifications

Maximum wrapping speed	25-30 loads/ Hour Speed
Max Wrapping Height	2000mm
Max Pallet Size	1.2m x 1.2m
Wrapping Speed	3-12RPM (Adjustable)
Standard Film Width	500mm
Constant Film Delivery Force	Standard
Standard Pre-Stretch	250% pre-stretch
Film Capacity	250mm Diameter
Machine Weight	800KG
Standard Pre-Stretch	300% pre-stretch
Film Capacity	250mm Diameter
Film Delivery System	Motor control
Up & Down Drive System	Belt drive
Top Pressure Function	Optional
Machine Size	2.68m x 1.1m x 3.1m
Machine weight	600KG
Voltage	220V/50/60HZ
Special Process	Introduction
Frame	Steel+Aluminum profile
Printing	Metallic Paint
Rotary Driveway	Slewing Bearing
Control	PCB Paxum
Position Sensor	SICK (Germany)
Photoelectric Sensor	Autonics
Travel Switch	OMRON (Japan)
Rotary Drive Motor	Paxum Brake Motor
Touch Screen	X-Line
Switch	Schneider
Up and Down Motor	Paxum

