



COMMERCIAL DRYER (FRONT CONTROL) FOR VENDED LAUNDRY APPLICATIONS

CD10EC



FEATURES

- **Superior airflow**
 - Advanced blower system produces airflow of 220 cu. Ft. per minute
 - Fast-drying results with advanced airflow pattern
 - Minimum dry time
- **Large capacity**
Large 7.0 ct ft. cylinder
- **Door opening of 2.06 sq. ft. for fast and easy loading and unloading**
- **Time savings**
Large, easy-clean lint filter is located upfront

CONTROL

- **Micro-Display Control (MDC)**
Offering the most essential features and programming options, the Micro-Display Control (MDC) on IPSO commercial dryers is user-friendly and features an attractive, easy-to-read design
- **Coin countdown start**
Displays vend price and countdown coin and cycle time
- **Touch pad control**
Offers touch pad selection and combines both temperature and cycle
- **Sound and light indicators**
Indicate cycle status and coin validation
- **Activation options**
Available with coin drop installed, card ready or coin ready models
- **Manual programming and audit**
Program and audit use via the control panel



visit laundrysolutions.com.au

Vended CD10C Front Control Dryer specifications

	CD10EC
Control Option	Micro-Display Control
Control Location	10° front
Drum	
Capacity (kg)	10
Volume (L)	198
Motor	
Power (KW)	0.25
Cabinet	
Cylinder Finish	Galvanized
Colours	White
Door Type	Solid
Heating	
Heat Source	Electric
Heating Power (KW)	4
Connection	
Gas Inlet Connection (mm)	N/A
Exhaust Outlet Diameter (mm)	102
Exhaust Airflow (L/sec)	105
Operation	
Cycles	4
Cycle Indicator Lights	Yes
Power	
Electrical Requirements	20 AMP/240/50/1
Transport Data	
Gross Weight (KG)	73
Net Weight (KG)	68
Dimensions (mm)	1126h x 683w x 711d
Packing Dimensions (mm)	1156h x 762w x 864d

* heights may slightly vary depending on the levelling adjustments

(MM)	A*	B*	C*	D*	E	F	G	H	I	J	K
CD10EC	1126	938	392	102	391	683	114	10	203	711	597

electric

