



AL36/E3



- » Suitable for mines, coal mines and sand conditions.
- » Special compound provides stronger cut and wear resistance.
- » Excellent mud expelled and side skidding resistance on mud, soft and slippery surfaces for improved self-cleaning, flotation and stability.

SIZE	TYPE	AL36	AL37	AE33	AE33	AE35	AE37	AE39	AE41	AE43	AE45	AE46	AE47	AE49	AE401	AE410	AG01
		E3	E3	E3	RT E3	E3	E3	E3	E4	E4	E4	E4	E4	E4	E4	E4	E4
14.00 R20 ***	TL/TT			●													
12.00 R24 ***	TT								●								
14.00 R24 ***	TL/TT			●													
13.00 R25 ***	TL/TT			●		●											
14.00 R25 ***	TL/TT			●	●	●									●		
15.5 R25 **	TL	●															
16.00 R25 **	TL/TT			●													
17.5 R25 **	TL	●	●														
18.00 R25 **	TL									●							
20.5 R25 **	TL	●	●														
23.5 R25 **	TL	●	●										●				
26.5 R25 **	TL	●	●										●				
29.5 R25 **	TL		●										●				
550/65 R25 **	TL					●											
650/65 R25 **	TL						●										
750/65 R25 **	TL						●										
18.00 R33 **	TL										●						
21.00 R33 **	TL											●					
21.00 R35 **	TL													●			
24.00 R35 **	TL										●						
27.00 R49 **	TL											●				●	
33.00 R51 **	TL																●

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

