The AFC 537 ICIP Blue Moon are retarder proofer cabinets, of one compartment one door, designed to receive trolleys or ladders.

- √ Humidity generator with electronic humidity probe.
- ✓ Panels insulated with polyurethane foam 42kg / m3, high pressure, 60 mm thickness, food-grade PVC coating.
- ✓ Door seals in black magnetized TPE.
- ✓ Door dampers.
- ✓ Reversible door.
- ✓ Batteries protected by a reinforced cataphoresis treatment.
- $\checkmark$  Door hinged on the right in standard (left on request).
- ✓ H.T.A. Refrigerating unit (High Ambient Temperature, +43°C max.) in standard.







## TECHNICAL DATA

	AFC 537
Dimension of trolley/ladder	550 x 850 x H1855
Entrance of trolley	550
Number of trolley/ladder	I
Useful dimensions	E590 x P880
Number of doors	I
Refrigerating unit	1/2 CV
Refrigerating capacity at -10°C	0,88 kW
Fluid	R448A
Voltage	220-240V ~IPH+N+T
Frequency	50 Hz
Connection	5 A

## IMPLANTATION







4	Power supply		0 0	Water supply		Sewage disposal	
Installation power	type of connection	height from the ground		dimension connection	height from the ground	type of connection	dimension connection
0,9 Kw	$\odot$	2,50 m	-₩	Ø15/21	2,50 m	<b>S</b>	Ø40mm



## OPTIONS AND ACCESSORIES

- Finishing: interior Stainless Steel 304 / exterior steel PVC
- Finishing: interior Stainless Steel 304 / exterior brushed Stainless Steel 430
- -VapooO option: reinforced steam system by boiler(only for AFC with stainless steel interior)
- Insulating anti-skid ground, 15mm, thickness, with a stainless steel access ramp (15mm to add to the total height of the cabinet)
- Delivered dismantled

