

## 02

Commercial  
Refrigeration**MONOBLOK COOLING**

Fast cooling and high efficiency. Save more space in cabinet and easy maintenance and cleaning

**EMBRACO COMPRESSOR**

Top level EMBRACO compressor to guarantee best cooling results

**EXTRA THICK INSULATION**

75mm thickness of insulation better heat preservation to reduce energy consumption

**DIXELL DIGITAL CONTROLLER**

Precise control and display the temperature

**FLAT INNER TOP**

More space to storage. More reasonable air circulation inside

**AMERICAN STYLE HANLE****SHELF AND GUIDE FOR GN FRIDGES**

The height of shelves is adjustable due to the size of stored products

**STRONG MAGNETIC GASKET**

Removable gasket for cleaning and replacement

**ROUND EDGE AND CORNER**

Food residual and water can be easily clean to reduce bacteria and guarantee the safety of food

**CASTOR WITH BRAKE**

## 02

Commercial  
RefrigerationCNOX UPRIGHT GN  
FRIDGE & FREEZER

Features	Model	Temperature	Power
<b>Monoblock cooling system</b> Fast cooling and high efficiency Save more space in cabinet, and easy maintenance and cleaning	CN1FDUC.GN	+ 0°C ~ + 6°C	240V/10A
	CN1FDUF.GN	-16°C ~ -20°C	240V/10A
	CN2FDUC.GN	+ 0°C ~ +6°C	240V/10A
	CN2FDUF.GN	-16°C ~ -20°C	240V/10A
<b>Dixell digital Controller</b> Precisely control and display the temperature of food due to user demand	Dim WxDxH (mm)	Liter	System
	700 x 820 x 2050 700 x 820 x 2050	550 550	Cooling Type : Ventilated Defrost Type : Automatic
<b>75mm Thick Insulation</b> 75mm Thick insulation, better heat prevention to reduce energy consumption	1400 x 820 x 2050	1220	
	1400 x 820 x 2050	1220	
<b>Refrigerant</b> Industry standard. Chiller : R134a Freezer : R404a			

Prices and specification are subject to change without notice. Product Drawings / Images are representative only and are for illustrative purpose, final product may differ.

Copyright © CN United 2019.  
All rights reserved.Contact AU: +61 413 901 398 | +61 449 919 866  
Contact MY: +603 - 5614 3922 | +603 - 5192 3922E-mail: [sales@cnunited.com.au](mailto:sales@cnunited.com.au)  
E-mail: [sales@cnunited.com.my](mailto:sales@cnunited.com.my)Web MY: [www.cnunited.com.au](http://www.cnunited.com.au)  
Web AU: [www.cnunited.com.my](http://www.cnunited.com.my)

## 02

Commercial  
RefrigerationCNOX UPRIGHT  
FRIDGE & FREEZERCN4DUC  
CN4DUFCN2DUC  
CN2DUF

Features	Model	Temperature	Power
<b>Monoblock cooling system</b> Fast cooling and high efficiency Save more space in cabinet, and easy maintenance and cleaning	CN2DUC	+ 0°C ~ +6°C	240V/10A
	CN2DUF	-16°C ~ -20°C	240V/10A
	CN4DUC	+ 0°C ~ +6°C	240V/10A
	CN4DUF	-16°C ~ -20°C	240V/10A
<b>Dixell digital Controller</b> Precisely control and display the temperature of food due to user demand			
<b>60mm Thick Insulation</b> Thick insulation, better heat prevention to reduce energy consumption	680 x 760 x 1965	500	Cooling Type : Ventilated Defrost Type : Automatic
	680 x 760 x 1965	500	
	1220 x 760 x 1965	1000	
	1220 x 760 x 1965	1000	

**Refrigerant**

Industry standard. Chiller : R134a  
Freezer : R404a

Prices and specification are subject to change without notice. Product Drawings / Images are representative only and are for illustrative purpose, final product may differ.

## 02

Commercial  
RefrigerationCNOX UPRIGHT GLASS DOOR  
FRIDGE & FREEZER

CN1GDC3E1



CN2GDC3E1



38°C ambience

EMBRACO  
compressorForced air  
circulationDefrosting by  
heating elementEvaporated  
by hot gasR134a / R404A  
R290

Features	Model	Temperature	Power
<b>Monoblock cooling system</b> Fast cooling and high efficiency Save more space in cabinet, and easy maintenance and cleaning	CN1GDC3E1	+ 0°C ~ +6°C	240V/10A
	CN2GDC3E1	+ 0°C ~ +6°C	240V/10A
<b>Dixell digital Controller</b> Precisely control and display the temperature of food due to user demand			
	Dim WxDxH (mm)	Liter	System
	680 x 760 x 1965	500	Cooling Type : Ventilated Defrost Type : Automatic
	1200 x 760 x 1965	1000	
<b>60mm Thick Insulation</b> Thick insulation, better heat prevention to reduce energy consumption			
<b>Refrigerant</b> Industry standard. Chiller : R134a			

Prices and specification are subject to change without notice. Product Drawings / Images are representative only and are for illustrative purpose, final product may differ.

Copyright © CN United 2019.  
All rights reserved.Contact AU: +61 413 901 398 | +61 449 919 866  
Contact MY: +603 - 5614 3922 | +603 - 5192 3922E-mail: [sales@cnunited.com.au](mailto:sales@cnunited.com.au)  
E-mail: [sales@cnunited.com.my](mailto:sales@cnunited.com.my)Web MY : [www.cnunited.com.au](http://www.cnunited.com.au)  
Web AU : [www.cnunited.com.my](http://www.cnunited.com.my)

## 02

Commercial  
RefrigerationCNOX  
FOR A BETTER KITCHENCNOX UNDER COUNTER  
CHILLER & FREEZERCN2DCC1200  
CN2DCF1200  
  
CN2DCC1500  
CN2DCF1500CN3DCC1800  
CN3DCF1800

43°C ambience

EMBRACO  
compressorForced air  
circulationDefrosting by  
heating elementEvaporated  
by hot gasR134a / R404A  
R290

Features	Model	Temperature	Power
<b>Removable monoblock cooling system</b> Fast cooling and high efficiency. Save more space in cabinet, and easy maintenance and cleaning	CN2DCC1200	+ 0°C ~ +6°C	240V/10A
	CN2DCF1200	-16°C ~ -20°C	240V/10A
<b>Dixell digital Controller</b> Precisely control and display the temperature of food due to user demand	CN2DCC1500	+ 0°C ~ +6°C	240V/10A
	CN2DCF1500	-16°C ~ -20°C	240V/10A
<b>60 Thick Insulation</b> Thick insulation, better heat prevention to reduce energy consumption	CN3DCC1800	+ 0°C ~ +6°C	240V/10A
	CN3DCF1800	-16°C ~ -20°C	240V/10A
<b>Refrigerant</b> Industry standard. Chiller : R134a Freezer : R404a	Dim WxDxH (mm)	Liter	System
	1200 x 700 x 840	250	Cooling Type : Ventilated Defrost Type : Automatic
1200 x 700 x 840	250		
	1500 x 700 x 840	340	
	1500 x 700 x 840	340	
	1800 x 700 x 840	440	
	1800 x 700 x 840	440	

Prices and specification are subject to change without notice. Product Drawings / Images are representative only and are for illustrative purpose, final product may differ.

Copyright © CN United 2019.  
All rights reserved.Contact AU: +61 413 901 398 | +61 449 919 866  
Contact MY: +603 - 5614 3922 | +603 - 5192 3922E-mail: [sales@cnunited.com.au](mailto:sales@cnunited.com.au)  
E-mail: [sales@cnunited.com.my](mailto:sales@cnunited.com.my)Web MY : [www.cnunited.com.au](http://www.cnunited.com.au)  
Web AU : [www.cnunited.com.my](http://www.cnunited.com.my)