

MC 1050-20TF

FEED TRACK CONVEYOR







A leading manufacturer of screening and conveyor equipment, offer the MC1050-20TF Feed tracked stacking conveyor, ensuring regular & consistent feed the MC1050-20TF is the ideal solution for jobs that require high production stockpiling or material transfer

Irish Manufacturing Services Limited 34a Dunroe Road, Clogher, Co. Tyrone, N. Ireland BT76 ODz

Tel. +44 (0)28 8554 9656 E-mail info@ims-ltd.ie website; www.ims-ltd.ie



HEAVY DUTY CONSTRUCTION

Constructed from 5mm thick MS plate designed in 500mm deep section to give added stability and to withstand the rigours of heavy duty operation.

FEED HOPPER

8 cubic metre capacity feed hopper with 4.5m wide target area to accept most loaders. Hopper lined with 6mm MS wear plates. 1050mm wide belt feeder with impact rollers, heavy duty belt and variable speed control.

DISCHARGE CONVEYOR

The conveyor is constructed in 3 sections, the tail section includes a standard reception hopper and the head section includes the conveyor drive, consisting of 2 Sauer-Danfoss hydraulic motors and rubber lagged drive pulley. The belt width is 1050mm and the overall length of the discharge conveyor is 20m.

DIESEL-HYDRAULIC POWER

The conveyor is powered by a Caterpillar C4.4 74 kw Diesel Engine coupled to a triple hydraulic pump giving sufficient oil flow to drive the variable speed belt feeder, the main discharge conveyor and the crawler tracks.

UNDERCARRIAGE

The undercarriage consists of the hydraulically operated crawler tracks together with an adjustable support trestle arrangement, which allows variation in both feed and discharge heights

HYDRAULIC FOLDING MECHANISM

The folding mechanism of the conveyor head section allows for quick site set up and provides a flexible approach to transport of the unit. The hydraulic folding is designed so that the hydraulic cylinder piston rods are fully protected when the machine is operational

EMERGENCY STOP SYSTEM

Every MC1050-20TF track Conveyor is equipped from the factory with an emergency stop system that will render the plant inoperable when activated, providing added safety for the operator.



STANDARD FEATURES

- Detachable Hopper to allow for container transport Hopper in 20' Container, Conveyor in 40' Container
- Extended foldable head section to give additional reach from tracks - 13m from front of tracks to discharge point
- Radio Remote Control Tracking
- ▶ 1050mm (42") wide Feeder and Main Belt
- ▶ 127mm (5") Impact Rollers under Feeder
- Mild Steel Replaceable Liner Plates in Hopper as standard
- Helmet Door on front of Hopper to regulate flow of material
- 8 cubic metre capacity Hopper
- Cartridge type Feeder Can be removed easily for maintenance
- User friendly hydraulic inclination (no pins required)
- Crawler Track Movement
- 74 kw Diesel-Hydraulic Drive
- ▶ 1050mm (42") wide 3 ply belt in both Feeder and Discharge Conveyor
- Hydraulic Folding on Head Section
- Hydraulic Raise and Lower



OPTIONS

- Remote Control Hydraulic Tipping Grid
- Single Deck Vibrating Grid
- Caterpillar C3.4B Tier 4 Engine
- Hardox 400 Wear Liners In Hopper
- Rear Low Loading Hopper
- ▶ Shredder on discharge from Feeder
- ► Heavy Duty Belt On Discharge Conveyor
- ► Chevron Belt On Discharge Conveyor
- Dual Power: Electric & Diesel / Hydraulic Power Unit
- PVC Covers



SPECIFICATIONS

Operational length	23.	.5M"	(77')

► Total weight 17000 kgs (37400 lbs)

Due to Irish Manufacturing Services Limited's policy of continuing product improvements, specifications are subject to change without notice or obligation. No representation is made that the products depicted herein comply with any laws, codes, rules, regulations or standards. Compliance is the responsibility of the user. Additional safety equipment may be required by the particular location and application of product.

Irish Manufacturing Services Limited

34a Dunroe Road, Clogher, Co. Tyrone, N. Ireland BT76 ODz

Tel. +44 (0)28 8554 9656 E-mail info@ims-ltd.ie website; www.ims-ltd.ie