



SQ40TCC

COMBI OVEN 40 TRAYS GN 1/1 -
20 TRAYS GN 2/1
5" CAPACITIVE TOUCH CONTROL
SELF CLEAN INTEGRATED



FUNCTIONAL CHARACTERISTICS

Display	5" CAPACITIVE TOUCH
Supply	ELECTRIC
Timer	-
Number of motors	4
Motor speeds	2
Max cooking temperature (°C)	260°C
Core probe	Single point PT1000
Cooking chamber material	AISI304
Opening door	Right handle
Chimney	50 mm motorized
Humidification	Direct injection
Air injection	-
Self-washing	Automatic

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Trolley GA 40/66
Max tray load	4 kg

DIMENSIONS

Oven size with handle WxDxH (mm)	1051 X 1248 X 1881
Oven size without handle WxDxH (mm)	1051 X 1184X 1900
Chamber size WxDxH (mm)	700 X 726 X 1496
Unit weight (Kg)	285,8

PACKAGING

Packaging	PALLET + CRATE
Packaging size WxDxH (mm)	1150 X 1345 X 2060
Unit weight with packaging (Kg)	395

ELECTRICAL DATA

HEATERS 10,5kW 50Hz - Single power supply	
Power	43,1kW
Frequency	50Hz
Power supply	380-415V 3N~



Amperage	65,8A
Power cord req.	5G25
HEATERS 10,5kW 60Hz Single power supply	
Power	43,7kW
Frequency	60H
Power supply (standard)	380-415V 3N~
Amperage (standard)	68,3A
Power cord req. (standard)	5G25
WATER CONNECTION REQUIREMENTS	
Humidification Water Inlet	3/4" GAS
Washing Water Inlet	10mm quick fitting
Water drain	2 x 30 mm
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa
CONSUMPTION	
Humidification Water (L/h)	16,7l/h max consumption
Rinse Water @2barG	35,5l
Short Washing Water @2barG	66,6l
Long Washing Water @2barG	139l
Short Washing Detergent *	468,8g
Long Washing Detergent *	669,7g
CONNECTIVITY	
USB	2.0
Bluetooth	-
Wi-Fi	-
Cloud	-
ACCESSORIES	
Self clean system kit	-
Oven stand	-
Hood (Air)	-
Hood (Water)	POSLMWF1 POSLMWF2
Core Probe	-
Proofer	-



Stacking kit for 2 ovens	-
Smoker	SMK02
Blast Chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	S1
Detergent 6KG	DT2
Detergent10KG	DT4

