





Features

- Adjustable film tension from control panel, via 100% electromagnetic brake.
- Auto film tension film tension begins after first rotation of pallet.
- Adjustable automatic photocell load height detection.
- Security foot guard for user protection.
- E-Go control panel.
- Top and bottom wrapping counter from 0-9 cycles.
- Turntable speed adjustable 1-12rpm, soft start and stop.
- Turntable stops in reset position.
- Chain driven turntable.
- Carriage speed adjustable from 0.5m/min 6m/min.

Functions

- Digital Panel with LED indicator for turntable/carriage speed, tension, wrapping counts and program mode.
- With two main wrapping programs, and three auxiliary programs, you can wrap each pallet to suit your specific needs.
 - Single/Double Wrapping
 - Reinforce/Unstable Object & Top Sheet Wrapping
- Memory setting function.
- Speed adjustment from panel for turntable and carriage.
- Reset and Over Wrapping function.
- Handle operation for turntable and carriage.
- Start/Stop push buttons.
- Large Emergency Stop button.

Specifications

Production Rate Max. 30 pallets/hour

Turntable Speed 12RPM **Turntable Diameter** 1500mm Max. Load Weight 2000kgs Max. Wrapping Height 2300mm **Shipping Weight** 400kg

Film Stretch Magnetic Brake Stretch

Film Stretch Rate

Wrapping Tension Digital Touch Panel Adjust

110V/220V (50/60Hz) **Electrical Requirements**

1KW

Standard **Photocell Sensor**

Operation Panel Digital Display and Touch Panel

Structure Full steel construction

Film Spec. 500mm wide, max outer diameter 250mm, Core

Diameter 76mm

Technical Data Operation Manual

Extra Options Turntable 1600mm / 1800mm

Wrapping Height 2500mm Pneumatic Top Pressure 2500kg Load Capacity 750mm wide Film Carriage

Access Ramp

Weighing Scales System

Warranty 1 Year











