

KEY FEATURES

Globe Power's GPFL200 Smart Flood Light uses the latest renewable technology to provide a cost-effective lighting solution that does not require diesel input.

This unit runs for a minimum of 24 hours and can be used across multiple shifts on site, comfortably power an event, or provide a dusk to dawn lighting solution for safety requirements.

- 7 day timer
- AC charger
- Level alarm
- Dusk sensor
- Fork pockets
- Lifting lugs



USER-FRIENDLY OPERATION INTERFACE

SOLAR & ADVANCED LITHIUM ION BATTERY

PORTABLE & EASY TO TRANSPORT

AUSTRALIAN DESIGNED & ENGINEERED

PRODUCT SPECIFICATIONS

GENERAL

Model	Smart Floodlight - GPFL200
Lumen Output	23,000
Mast Height	5 Metres
Mast Type	Cable winch
Lights	2 x 100w LED Modules
Coverage	3,700m ² at 5 lux

OPERATIONAL DATA

Wind Rating	100km/h
Working Temperature	0 to 50°C
Light Bar Tilt	0 to 60°
Solar Orientation	0 to 360°

BATTERY

Battery	2.6kWh Lithium Ion (LFP)
Run Time	24-60 hours
Solar	340Wp
Solar Tilt	0° to 90°
Solar Efficiency	1 hr of sun/3.5 hrs of light

UNIT INFORMATION

Dimensions (Stowed)	1000 x 1000 x 2900 (LxWxH)
Dimensions (Deployed)	1700 x 1000 x 5800 (LxWxH)
Weight	850kg

