



Dr. Mach
medical lighting+technology


Mach LED 110

Compact spot light with
LED-technology



Mach LED 115

Compact spot light with
LED-technology





Spot light Mach LED 110

with 30,000 lux (0.5 m distance)

Rail model with fixation clamp for supply rails

Wall model with wall fixation

Mobile model on five feet mobile stand

Technical Data (1)

Mach LED 110 light system

Light intensity at 0.5 meter distance
 Colour temperature
 Colour rendering index $R_a^{(2)}$
 Size of the light field
 Diameter of the lamphead
 Temperature increase in the head area
 Number of LEDs
 Life-span of the LEDs

Mach LED 110

30,000 lux
 4,000 kelvin
 97
 10 cm
 12 cm
 0.5 °C
 3
 60,000 h

(1) Further technical details in the data sheet of the lamp, available upon request.
 (2) R_a is an average of R_1 = burnt pink, R_2 = mustard yellow, R_3 = yellow green, R_4 = light green, R_5 = turquoise blue, R_6 = skyviolet, R_7 = violet, R_8 = lilac. Maximum value = 100.



Spot light Mach LED 115

with 60,000 lux (0.5 m distance)

Rail model with fixation clamp for supply rails

Wall model with wall fixation

Mobile model on five feet mobile stand with one-hand height adjustment

Technical Data (1)

Mach LED 115 light system

Light intensity at 0.5 meter distance
 Colour temperature
 Colour rendering index $R_a^{(2)}$
 Size of the light field
 Diameter of the lamphead
 Temperature increase in the head area
 Electronic light intensity control
 Number of LEDs
 Life-span of the LEDs

Mach LED 115C

60,000 lux
 3,700; 4,000; 4,300 kelvin
 97
 11 cm
 22 cm
 0.5 °C
 standard
 7
 60,000 h

Mach LED 115

60,000 lux
 4,000 kelvin
 97
 11 cm
 22 cm
 0.5 °C
 standard
 7
 60,000 h

(1) Further technical details in the data sheet of the lamp, available upon request.

(2) R_a is an average of R_1 = burnt pink, R_2 = mustard yellow, R_3 = yellow green, R_4 = light green, R_5 = turquoise blue, R_6 = skyviolet, R_7 = violet, R_8 = lilac. Maximum value = 100.



Dr. Mach LED-technology


Superiour colour rendition

With an outstanding colour rendering index $R_a = 97$ the surgeon recognizes clearly the tiniest nuances of colour in tissue. The colour spectrum of the surgical field is rendered naturally with rich contrast. The OT-light clearly provides welcome relief for your eyes.



Facetted multi-lens system

Several computer-calculated facetted lenses (seven for the Mach LED 115 / 115C and three for the Mach LED 110) guarantee homogeneity and lowest shadiness in the light field. Separately arranged optical systems, each with one LED module, generate their own light field, which increases the contrast effect. Light intensities of 60,000 lux (Mach LED 115 / 115C) or up to 30,000 lux (Mach LED 110) at a distance of 0.5 meters can be attained without difficulty.



Control panel on the power pack housing (only Mach LED 115 / 115C)

The following light functions can be controlled on the power supply unit housing:

- Switching on / off (mechanical)
- Electronic brightness control
- Color temperature adjustment (only Mach LED 115C)




Handling

During development high attention was paid to easy handling and high ease of maintenance. Furthermore the flow-enhancing ring form and the minimal surface avoid any heat increase in the surgeon's head area and create a perfect laminar flow performance. The light can be positioned exactly to the wound field.



Long life-span/low power consumption

The life-span of more than 60,000 operating hours reduces the costs for exchanging and replacing the illuminants considerably, compared with the conventional halogen technology used with former OT-lights. By implementation of the LED technology the power consumption could be reduced with more than 50% to conventional halogen lights.



Cool light

The LED technology is much more efficient than conventional light sources such as halogen bulbs. The heat radiation is reduced to a minimum without using any expensive filter technique. The temperature increase in the surgeon's head area is imperceptible.

Dr. Mach GmbH & Co. KG

Floßmannstraße 28
85560 Ebersberg
Germany

Phone: +49 (0) 8092 / 20 93-0

Fax: +49 (0) 8092 / 20 93-50

E-mail: info@dr-mach.de

Please visit our website www.dr-mach.de