



IPSO®

# COMMERCIAL STACK WASHER/DRYER FOR ON-PREMISES LAUNDRY APPLICATIONS

## CS10E - CS10G



### FEATURES - WASHER

- **Stainless steel inner and outer drum** for long-lasting worry-free performance
- **Four-compartment soap box** for wash, pre-wash, bleach and softener
- **Dynamic Balancing System**
  - Suspensions & out-of-balance logic manages and redistributes unbalanced loads
  - Quiet operation
- **High-speed extraction**  
A 1200 RPM extract speed delivers 440G
- **Door opens 180°** for easy loading and unloading
- **Large capacity**
- **Ultra-low water use** of only 51.78 L per cycle

### FEATURES - DRYER

- **Superior airflow**  
Fast-drying results with advanced airflow pattern  
Minimum dry time
- **Large capacity**  
Large 7.0 ct ft. cylinder
- **Time savings**  
Large, easy-clean lint filter is located upfront

### CONTROL

- **Micro-Display Control (MDC)**
  - Four cycle options
  - Cycle time countdown
  - LED progress indicators
- **5 wash programs with possibility of programming cycle modifier options**
  - Added prewash
  - Extra wash time
  - Extra rinse
- **4 drying programs**



visit [laundrysolutions.com.au](http://laundrysolutions.com.au)

# OPL CS10 Stack Washer/Dryer specifications

	CS10E	CS10G
Control Option	Micro-Display Control	Micro-Display Control
Control Location	10° front	10° front
Drum		
Capacity (kg)	Washer: 10 / Dryer: 10	Washer: 10 / Dryer: 10
Volume (L)	Washer: 96.8 / Dryer: 198	Washer: 96.8 / Dryer: 198
Drum Speed		
G-Force	440	440
Spin Speed (RPM)	1200	1200
Motor		
Power (kW)	Washer : 0.67 / Dryer : 0.25	Washer : 0.67 / Dryer : 0.25
Cabinet		
Cylinder Finish	Washer: Stainless Steel / Dryer: Galvanized	Washer: Stainless Steel / Dryer: Galvanized
Colours	White	White
Door Type	Window / Window	Window / Window
Heating		
Heat Source	Washer: N/A / Dryer: Electric	Washer: N/A / Dryer: Gas
Heating Power	Washer: N/A / Dryer: 4 kW	Washer: N/A / Dryer: 26.37 mJ
Connection		
Gas Inlet Connection (mm)	N/A	9.5
Exhaust Outlet Diameter (mm)	102	102
Exhaust Airflow (L/sec)	105	105
Water Inlet (mm)	19	19
Water Pressure (BAR)	1.4/8.3	1.4/8.3
Water Consumption (L)	51.78	51.78
Drain	Pump Drain	Pump Drain
Operation		
Cycles	Washer: 5 / Dryer: 4	Washer: 5 / Dryer: 4
Cycle Indicator Lights	Yes	Yes
Power		
Electrical Requirements	Washer: 10 AMP/240/50/1 Dryer: 20 AMP/240/50/1	Washer: 10 AMP/240/50/1 Dryer: 10 AMP/240/50/1
Transport Data		
Gross Weight (KG)	189	189
Net Weight (KG)	175	175
Dimensions (mm)	1986h x 683w x 704d	1986h x 683w x 704d
Packing Dimensions (mm)	2032h x 762w x 864d	2032h x 762w x 864d

(MM)	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
CD10E	1678	1447	597	213	610	203	391	938	371	813	683	1986	1184	52	705	38	333	-	-
CD10G	1678	1447	597	213	610	203	391	59	938	371	1140	813	683	1986	1184	52	703	38	333

