



MODEL Q70PC/IND800

CODE

CR1012919

### 4 HEAT ZONE INDUCTION COOK TOP

## **QUEEN7**

- 15/10 worktop thickness
- · Stainless steel, Scotch-Brite finish
- · Sturdy and powerful with compact design
- Depth of 700 mm means it will fit the most common configurations
- Catalogue offers more than 300 standard models
- · Worktop, base cabinet and oven Versions
- Twin-piece knobs prevent the infiltration of dirt and are watertight
- Gas kitchens having burners with various configurations and power ratings: 3.5 kW - 5.7 kW - 7.0 Kw
- · Wide range of accessories



# Technical / functional characteristics

- · Watertight shatterproof glass-ceramic top.
- · Cooking zones marked with a 23 cm diameter circular screenprint.
- 3.5 kW single zone power.
- · Presence detector device and overheat device.
- · Heat mode activity indicator light.

DIMENSIONS	
Width (mm)	800
Depth (mm)	700
Height (mm)	250
Gas connection (Ø)	
Electric connection (V/~/Hz)	400V/3N 50-60 Hz
Cold water connection (Ø)	
Hot water connection (Ø)	

Cold soft water connection (Ø)	
Drain (Ø)	
Gas power (Mj/hr)	
Electric power (kW)	14
Plate dimensions (mm)	
Tank capacity (L)	
Tank dimensions (mm)	
Internal oven dimensions (mm)	





**MODEL** 

baron


Q70PC/IND800

CODE

CR1012919

# SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR

#### MISURE IN mm - DIMENSIONS IN mm - ABMESSUNGEN IN mm MESURES EN mm - MEDIDAS EN mm - MATEN IN mm



Legenda - Legende - Key - Légende - Leyenda - Legenda

E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief Presse étoupe de câble él. - Pisacable - Elektrische kabelwartel

H2O\* Attacco arrivo acqua - Wasseranschluss - Water inlet Arrivée eau - Union de agua - Wateraansluiting EN ISO 228-1 G 3/4