

## Pharmacy Refrigerators S Series

The Pinnacle purpose built pharmacy refrigerators have been designed in Australia to meet vaccine storage guidelines. Ideal for pharmacies and hospitals, they provide reliable temperature control and are easy to use.

### Features:

- ✓ **QCPP approved**
- ✓ **+2°C to +8°C operating temperature range**  
With exclusive Blue Bottle product temperature simulation <sup>2</sup>
- ✓ **Digital controller** <sup>1</sup>  
With battery backup providing 24 hours of temperature readings during power outage
- ✓ **Alarm system**  
Alarms when door open and/or out of temperature range
- ✓ **Continuous temperature logger**  
With easy USB download
- ✓ **Building Management System (BMS) connection**
- ✓ **Fan forced cooling**
- ✓ **Internal fan switch**  
Will turn off fan when door open
- ✓ **Energy efficient and quiet**  
Double glazed Low-E glass doors and superior insulation
- ✓ **LED lighting**
- ✓ **Door lock**
- ✓ **Cable port**
- ✓ **Cyclic defrost**
- ✓ **Warranty**  
1 year labour and 2 years parts



### Optional Features:

- Low temperature cut-out
- 4G SMS Auto-dialler
- Additional wire coated shelving
- Guardian T alarm testing system
- 7 day chart recorder



# Pharmacy Refrigerators S Series



## Technical Specifications

Model	PPR-S-36-1-GD	PPR-S-66-1-GD	PPR-S-145-1-GD	PPR-S-300-1-GD	PPR-S-430-1-GD
Storage capacity (litres)	36L	66L	145L	300L	430L
Voltage	220 VAC - 240 VAC 50Hz				
Amperage	0.8 Amps	0.8 Amps	1.05 Amps	1.5 Amps	1.7 Amps
Size external (W x D x H)	450mm x 470mm x 535mm	450mm x 470mm x 730mm	610mm x 610mm x 820mm	610mm x 655mm x 1500mm	610mm x 700mm x 1870mm
Weight	27kg	29.5kg	43kg	72kg	84kg
Refrigerant	R134a				
Warranty Labour (refer to full warranty conditions)	1 Year				
Warranty Parts (refer to full warranty conditions)	2 Years				
Number of shelves	2 + Base	2.5 + Base	3.5 + Base	6 + Base	8 + Base
Alarm points	+2°C to +8°C				
QCPP approved	x	x	✓	✓	✓
Digital controller with LCD display	Included				
Battery back up on controller					
USB download data logging					
Door open alarm					
High temperature alarm					
Low temperature alarm					
Power loss alarm					
Remote alarm contacts (BMS)					
Internal fan switch					
Cable port hole					
Fan Forced cooling					
Door lock and keys	Included				
High efficiency insulation					
Glass door with double layer Low-E glass					
Self closing doors					
LED lighting					
Defrost	Cyclic				
Guardian T alarm testing facility					
External temperature logger					
7 day chart recorder					
Low temperature cut out					
Auto dialler	Optional				
Additional shelving					
Customised shelving					
Solid door					
External construction	Colorbond® Steel				
Door hinge right-hand open	Standard				
Door hinge left-hand open	Optional				
Adjustable feet	Included				
Power cord length	2.5m				

Authorised Sales Agent



P: 1300 358 045  
F: (07) 3376 5433  
E: sales@cskgroup.com.au  
W: cskgroup.com.au



The Pharmacy  
Guild of Australia