

PLATINUM SERIES SPLIT POT GAS TUBE FRYER

AGP55TC



IECHNICAL DAIA:

Total Gas Supply

Dimensions (W x D x H): 397 x 876 x 1172

Total Weight: 104Kg

Cooking Area (W x D x H): 177 x 127 x 356mm (x2)
Oil Capacity: 9-11 Litres per pan

GAS DETAILSNatural Gas (NG)Universal LP Gas (ULPG)Minimum Supply Pressure1.7 kPa2.74 kPaOperating Pressure1.0 kPa2.5 kPa

88MJ/Hr

3/4" BSP connection

88MJ/Hr

NOTE: It is the responsibility of the installing gas plumber to ensure correct supply and connection sustaining appropriate pressure when all appliances are full on.

240 Volt 10Amp connection required to run control board.











Due to continuous product research and development, the information contained herein is subject to change without notice. Revision: 7/2/2020

www.stoddart.com.au www.stoddart.co.nz **PROJECT**

ITEM

QUANTITY

DATE

The Platinum series gas fryer are high efficiency fryers that deliver optimum performance while using minimal gas. Platinum fryers are supplied standard with Anets Platinum burner technology incorporating a highly efficient Energy Star® rated atmospheric burner recovery up to 70% thermal efficiency and lower flue temperatures. The patented burner incorporates a daily self-cleaning cycle, keeping burners tuned to operate in the most energy efficient manner.

FEATURES & BENEFITS:

- 4 x 102mm deep tube burners
- Energy Star® rated Platinum tube burners
- Tank Stainless steel construction
- Cabinet Stainless steel front, door & sides galvanised back
- Computer control with melt cycle and bail out modes. Complete with backup solidstate controller which can be switched on should the digital control fail.
- Cooking capacity of approximately 20kg of frozen 10mm fries / 24kg of frozen french cut fries per hour per tank
- Supplied with 2 x 165mm wide nickle plated wire fryer baskets, removable stainless steel basket support, lid, drain pipe extension & clean out rod
- · 10 year warranty on stainless steel frypot

OPTIONAL EXTRAS:

- Fry basket alternatives (twin, tripple, fine mesh, fish plates etc)
- Capping strips & Splashguards
- 152mm (6") fixed and swivel castors with brakes
- Computer control to substitute digital control
- Basket lifters
- Heat tape



