

# JETFIRE®

[www.oemgroup.com.au](http://www.oemgroup.com.au)

## Direct Fired Industrial Diesel Heater DC30

### Technical Specifications

Fuel Supply	Diesel / Kerosene
Heat Output	30 Kw
Fuel Consumption	2.40 Kg/h
Airflow	357 m <sup>3</sup> /h
Electricity Supply	Single Phase – 230 Volts
Connected Load	190 W
Minimum Room Vol.	250 m <sup>3</sup>
Running Time	12.6 Hours
Fuel Tank Capacity	18 Litres
Manufactured in Korea to Australian Specifications & Standards	

### Included Features

Steel Construction – Tank & Body	
Portable with Carry Handle	
Robust & reliable	
Inbuilt Safety Features:	<ul style="list-style-type: none"><li>➤ Temperature Limit Control</li><li>➤ Electrical System Protection</li><li>➤ Flame Out Sensor</li></ul>
Run time fuel gauge	
LED On/Off switch with Silicone cover	



Call us: 9270 0200  
For more info



Ad: [494-496 Great Eastern Highway, Redcliffe WA 6104](http://494-496%20Great%20Eastern%20Highway,%20Redcliffe%20WA%206104)  
Ph: (08) 9270 0200  
E: [contactoem@oemgroup.com.au](mailto:contactoem@oemgroup.com.au)

# JETFIRE®



<b>Model</b>	DC17
<b>Fuel Supply</b>	Diesel/Kerosene
<b>Heat Output</b>	17kW
<b>Fuel Consumption</b>	1.37 kg/h
<b>Air Flow</b>	357m³/h
<b>Electricity Supply</b>	230V 1 phase 50 Hz
<b>Connected Load</b>	140W
<b>Minimum Room Volume</b>	145m³
<b>Running Time (approx.)</b>	11h
<b>Fuel Tank Capacity</b>	19L

<b>Model</b>	DC30
<b>Fuel Supply</b>	Diesel/Kerosene
<b>Heat Output</b>	30kW
<b>Fuel Consumption</b>	2.40 kg/h
<b>Air Flow</b>	765m³/h
<b>Electricity Supply</b>	230V 1 phase 50 Hz
<b>Connected Load</b>	190W
<b>Minimum Room Volume</b>	250m³
<b>Running Time (approx.)</b>	12.6h
<b>Fuel Tank Capacity</b>	38L



<b>Model</b>	DC50
<b>Fuel Supply</b>	Diesel/Kerosene
<b>Heat Output</b>	50kW
<b>Fuel Consumption</b>	4.12 kg/h
<b>Air Flow</b>	1036m³/h
<b>Electricity Supply</b>	230V 1 phase 50 Hz
<b>Connected Load</b>	280W
<b>Minimum Room Volume</b>	420m³
<b>Running Time (approx.)</b>	9.4h
<b>Fuel Tank Capacity</b>	49L



<b>Model</b>	DI16
<b>Fuel Supply</b>	Diesel/Kerosene
<b>Heat Output</b>	16.5kW
<b>Fuel Consumption</b>	1.37 kg/h
<b>Electricity Supply</b>	230V 1 phase 50 Hz
<b>Connected Load</b>	70W
<b>Minimum Room Volume</b>	145m³
<b>Running Time (approx.)</b>	6h
<b>Fuel Tank Capacity</b>	13L



Ad: [494-496 Great Eastern Highway, Redcliffe WA 6104](https://www.google.com/maps/place/494+496+Great+Eastern+Highway,+Redcliffe+WA+6104)  
 Ph: (08) 9270 0200  
 E: [contactoem@oemgroup.com.au](mailto:contactoem@oemgroup.com.au)