



### TECHNICAL DATA

|   |                               |
|---|-------------------------------|
| Power cord                              | 15 A single phase plug & lead |
| Wash tank temperature                   | 55–60°C                       |
| Rinse water temperature (booster tank)  | Minimum 82°                   |
| Low temp cut-out (thermostop) activated | Yes                           |
| Cycle times                             | 60 sec.<br>120 sec.           |
| Water consumption                       | 2.0 litres                    |
| Tank capacity                           | 10 litres                     |
| Tank heating                            | 1.8 kW                        |
| Power supply                            | 240/50/1 – 15 A               |
| Booster loading                         | 1.9 kW                        |
| Total loading                           | 2.1 kW                        |
| Pump capacity                           | 180 watts                     |
| Loading height                          | 308 mm                        |

### PRODUCT ADVANTAGES

- Easy-to-use electronic controls with 2 cycles - 60 & 120 seconds
- Re-circulating & low 2.0 litre rinse volume glasswasher
- Digital temperature gauges
- Suitable for all glass, cup and light duty washing applications
- Designed to suit racks 400x400mm & 17"x14"
- Double skinned door for strength and durability
- Polypropylene wash & rinse arm with patented WIDE ANGLE FAN nozzle to maximise wash & rinse performance
- Wash pump inlet strainer to ensure machine reliability
- "Connect & use"- fill and drain hoses, pump-out drain, chemical dispensers and power lead / plug included for quick and easy installation
- Standard with 150mm stainless steel adjustable legs
- Includes 1 x 17"x14" glass rack,
- Back flow prevention device as standard to meet Watermark Approval and ATS 5200.101
- NOT SUITABLE FOR USE WITH REVERSE OSMOSIS SYSTEMS
- MADE IN GERMANY

# INDUSTRY KITCHENS

[www.industrykitchens.com.au](http://www.industrykitchens.com.au) 1800 611 058

\*Thermostop guarantees required temperatures with cold water and / or 240 V connection, the actual cycle times extend accordingly.

For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or an external water softener of the product line HYDROLINE PROTECT.

### DIMENSIONAL DRAWING

#### CONNECTIONS

|                               |                                 |
|-------------------------------|---------------------------------|
| ① Drain hose                  | 2,000 mm   ID20/OD25            |
| ② Supply hose                 | 2,000 mm   R 3/4"               |
| Required flow rate            | 5 l/min                         |
| Flow pressure                 | 0.5 (0.8 with softener) – 6 bar |
| Max. supply water temperature | 60 ° C                          |
| ③ Power cord                  | 2,000 mm                        |
| Supply hose for               |                                 |
| ④ Detergent                   | 2,500 mm                        |
| ⑤ Rinse aid                   | 2,500 mm                        |

