

CLADBOY

CladBoy
Australia



VACUUM LIFTING DEVICE FOR
ROOF- AND WALL PANELS



Configuration for roof panels



CLADBOY AUSTRALIA
ABN 186 2622 5998
PO BOX 2574
3 CORPORATE AVE ROWVILLE VIC 3178

Ph: 03 9754 0399 Fax: 03 9755 6071
www.cladboy.com.au

VIAVAC-CB

'CLAD BOY'

LIFTING EYE

CONFIGURATION FOR WALL PANELS

SOLID GRIPS

STORAGE BOX

Connection cable
battery charger

VACUUM GAUGE

Red-green indication

FILTER

QUICK COUPLINGS

To connect vacuum hoses

LOCKING PIN

To lock the main traverse
in the end position

INDICATION

Battery charging level

CONTROL

Suction and release
with safety latch

CASING

For the electric components

POSSIBILITIES

With the option of various suction pads and extension kits, the machine is unique flexible and versatile and can be used for many applications such as:

- Horizontal wall panels
- Vertical wall panels
- Flat or inclined roof panels

The standard suction pads are suitable for all commonly used sandwich roof and wall panels. For other profiles such as corrugated and roof tile profile, special suction pads are available.

SAFETY FEATURES

- Clear audible low vacuum warning
- Large vacuum buffer tank
- Low battery warning
- Secondary safety device

SPECIFICATION

- Lifting capacity max. 500 kg
(depends on applied suction pads)
- Machine weight min. 125 kg
(depends on used configuration)

**COMPACT AND DURABLE
POWERED BY INTERNAL
RE-CHARGEABLE BATTERY**

SUCTION PADS
With exchangeable seals

MAIN TRAVERSE
90° rotateable



EASY TO TRANSPORT

Complies with European standard EN 13155



CLADBOY AUSTRALIA
ABN 186 2622 5998
PO BOX 2574
3 CORPORATE AVE ROWVILLE VIC 3178

Ph: 03 9754 0399 Fax: 03 9755 6071
www.cladboy.com.au