BLUE SEAL EVOLUTION SERIES®

Technical data sheet for VEE RAY SINGLE PAN GAS FRYER 600mm

- GT60-HPO
- 140 MJ/hr continuous production single pan fryer
- High Power Output infra-red burner system
- Easy clean stainless steel open pan with 10 year limited warranty
- 31L oil tank capacity
- 2 large or 3 standard basket capacity
- Large capacity cool zone
- 32mm (1 ¹/₄") drain valve
- Rear rollers
- Stainless steel exterior
- Easy service •
- Fully modular •



Overall Construction

- Stainless steel pan with 10 year limited warranty
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- Vitreous enamelled control panel
- 32mm (1 ¹/₄") drain valve
- 63mm dia. heavy-duty 1.2mm 304 stainless steel adjustable legs at front and two rollers at rear
- 2 large standard baskets and stainless steel lid supplied standard

Controls – Burner System

- Electronic thermostat
- Large easy use control with easy view scale
- Thermostat range 90 195°C
- Over-temperature safety cut-out
- Full electronic ignition system
- Two 70MJ/hr power infra-red burners
- Independent LH and RH burner systems
- Lock-out alarm indicators on front panel

Cleaning and Servicing

- Open stainless steel pans for easy clean
- Easy clean basket support bar
- 32mm (1 ¹/4") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit



Technical data sheet for VEE RAY SINGLE PAN GAS FRYER 600mm

Specifications Production rate 50kg/hr

Pan Size

Width 515mm Length 380mm Oil frying depth 95mm Oil capacity 31L (46.5lbs shortening)

Baskets

2 chrome plated large wire baskets 210mm W x 335mm D x 145mm H Optional 3 chrome plated standard wire baskets 145mm W x 335mm D x 145mm H Stainless steel perforated basket support plate

Burners 2 x 70MJ/hr power infra-red burners

Gas Power 140MJ/hr, 39kW

Gas connection R ³/4 (BSP) male Optional rear connection (refer specification drawing)

Electrical Connection 230-240 Vac, 1P+N+E, 50/60Hz, 0.5A 3 pin 10A pluq cordset fitted

Dimensions

Width 600mm Depth 812mm Height 915mm Incl. splashback 1085mm

Nett weight 100kg

Packing data 0.70m3, 148kg

Width 870mm Depth 645mm Height 1255mm


Gas types


Available in Natural gas and LP gas, please specify when ordering Units supplied complete with gas type conversion kits Other gas types on request

Options

Adjustable feet at rear Filtamax Filtration System Fish plates Extra large baskets Standard baskets Side splash guards Joining caps Castors

GT60-HPO





MOFFAT

Australia www.moffat.com.au New Zealand www.moffat.co.nz

www.bluesealevolution.com

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 gldsales@moffat.com.au

Western Australia Telephone 08-9202 6820 bgarcia@moffat.com.au

New Zealand Moffat Limited

Christchurch 16 Osborne Street Christchurch 8011 Telephone 03-389 1007 Facsimile 03-389 1276 sales@moffat.co.nz

Auckland Telephone 09-574 3150 sales@moffat.co.nz





ISO9001 Quality Management Standard

signed and manufactured by

MOFERT

ISO9001 All Blue Seal products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.



VEERAY

AGA 🐨 Cert 6125 In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and

Printed in China © Copyright Moffat Ltd Moffat / 7.09 / 1140

BLUE SEAL EVOLUTION SERIES®