

INTEGRAL TWIN

3946UAP150R36-32S30

EAN 4031582355086

Swivel castor with central total lock, frame made of pressed steel, precision ball bearing in swivel head, housing with synthetic cover, stem with cam hole for profile bars, short version. Wheel centre made of Polyamide, Tread: Polyurethane, precision ball bearing



BETTER MOBILITY. BETTER LIFE.



Picture may differ from original product

Technical Data

| | |
|------------------------|----------------|
| Wheel diameter | 150 mm |
| Width of Tread | 15 mm |
| Castor width | 74.5 mm |
| Bolt-Ø | 32 mm |
| Bolt length | 50 mm |
| Offset | 45 mm |
| Swivel Interference | 240 mm |
| Overall height | 193 mm |
| Temperature | - 30 / + 80 °C |
| Standard | EN 12531 |
| Swivel Radius | 120 mm |
| Hardness of tread | Shore D 40 |
| Load capacity | 250 kg |
| Load capacity (static) | 500 kg |

Advantages at a glance

| | |
|----------------------|-----------|
| Roll performance | ● ● ● ○ ○ |
| Movement noise | ● ● ● ○ ○ |
| Attrition | ● ● ● ● ○ |
| Corrosion resistance | ● ● ● ○ ○ |