




Let's grow together 

QDD25P

Electric tractor 2.5t

MITACO EQUIPMENT CO.,LTD
www.mitaco.com.au

Electric tractor 2.5t QDD25P

Distinguishing mark					
1.1	Manufacturer		MITACO		
1.6	Model designation		QDD25P		
1.7	Drive unit		Electrics		
1.8	Operator type		pedestrian		
1.9	rated capacity	Q	kg	450	
1.7	Rated drawbar pull	F	kg	2000	
1.9	Wheelbase		mm	1055	
Weight					
2.1	Service weight include battery		kg	750	
2.2	Axle loading, laden driving /loading		kg	640/560	
2.3	Axle loading, unladen driving /loading		kg	450/300	
Types,Chassis					
3.4	Tyre type driving wheels/loading wheels			solid rubber	
3.5	Tyre size, driving wheels	diameter	width	mm	4.00-8
3.6	Tyre size, loading wheels	diameter	width	mm	15 x 4.5
3.7	Wheels, number driving/loading (x=drive wheels)			mm	1 /2x
3.7	Track width, rear, loading side	b ₁₁	mm		664
Dimensions					
4.7	Height of overhead, No ladder	h ₆	mm		1265
4.8	Height of overhead, Ladder with 3 stairs		mm		1940
4.9	Height of overhead, Ladder with 5 stairs		mm		2480
4.12	Tow coupling height	h ₁₀	mm		320
4.13	Loading height, unladen	h ₁₁	mm		590
4.16	Length of loading surface	l ₃	mm		1300
4.18	Width of loading surface	b ₉	mm		740
4.19	Overall length, No ladder	l ₁	mm		2190
4.20	Overall length, Ladder with 3 stairs		mm		2300
	Overall length, Ladder with 5 stairs		mm		2400
4.21	Overall width	b ₁ / b ₂	mm		780
4.32	Ground clearance, center of wheelbase	m ₂	mm		71
4.35	Turning radius	wa	mm		1385
Performance data					
5.1	Travel speed, laden/ unladen		km/ h		7/7
5.5	Drawbar pull, laden/unladen		N		640
5.6	Max. drawbar pull, laden/unladen		N		2500
5.7	Gradeability, laden/unladen		%		5/20
5.10	Service brake type				Hydraulic+Mechanical
Electric-engine					
6.1	Drive motor rating S2 60 min		kW		3
6.3	The maximum allowed size battery		mm		/
6.4	Battery voltage/nominal capacity K5				48/200
6.5	Battery weight		kg		200
Addition data					
8.4	Sound pressure level at the driver's ear		dB (A)		70
8.5	Traction pin type		dB (A)		Bolt type

- The parameters in the table are of the standard model. For more information, please contact us.
- The parameters are subject to change without notice.

