

Data sheet: Fillogy Chunky M (Art. 301010)

Description

Machine for dosed filling of flowable and chunky (also hot) products e.g.:

- jam (might incl. pieces up to 7mm)
- mustard (fine and granular), ketchup
- fruit sauces, barbecue-sauces
- creamy yoghurt with fruit pieces

Main field of application: filling of container sizes from 50 to 500 g



Customer benefit

Precise and effective dosing of products and fast product change

Operating conditions

Hours of operation per day: 8
 Days of operation per week: 5
 Ambient temperature: 10 - 40°C

Technical Data

Nominal voltage: 24 V DC (Power supply for 220 V included)
 Power consumption: 80 - 240 W
 Motor speed: 14 - 100 U/min
 Footprint: Width 350 mm x Length 350 mm
 Total height: 700 mm (optional 1,000 mm)
 Height under filling nozzle: 10 - 375 mm
 Weight: 14.5 kg (without power supply)
 Dosage with step size

- 0.1 g: 0.1 - 49.9 g
- 1.0 g: 50.0 - 32,500.0 g

 Filling accuracy: Max. 2% deviation
 Maximum suction lift: 1,500 mm
 Maximum volume flow: 4.5 l/min
 Filling temperature: 2 - 95°C

Triggering of the filling process

Foot switch (included)
 Frame switch (included)
 Sensor (optional for operation with rotary table)

Automatability

In part