





Features

- High efficiency and low energy consumption
- Remote Controlled System
- Automatic Photoelectric sensor detects pallet height
- Automatic film cut and clamp function
- Multi-layer function: This function can set different wrapping cycles and wrapping tension at any height, up to 9 layers per pallet.
- 400% pre-stretch film rate
- Advanced Safety Technology Safety device under film carriage to protect the foot or head of the operator
 - Transparent panel makes it easy to find problem without opening door.
 - Up and down belt deviation and damaged alarm system
- High quality electrical components
- LCD Touch Operating System
- Automatic Rope Grip System
- Soft start and soft stop
- Intelligent Alarm system with LED Indicator
- 1650mm turntable
- 2350mm wrapping height
- Max load weight: 2000KG
- 1 Year Warranty



20-25 loads/hour **Production Rate Turntable Speed** 3-12RPM(Adjustable)

Turntable Diameter 1650mm Max. Load Weight 2000kgs Std. Wrapping Height 2350mm

Pre-stretch Rate 400% pre-stretch maximum

1.5 ~5.5 m/mins **Up & Down Speed**

240V Voltage **Machine weight** 680kg

Machine size L2710mm*W1650mm*H2720mm

Film Spec. 500mm wide, 250mm diameter, 76mm core diameter

PLC Siemens **Compressed Air** Nο

Technical Data Operation Manual

Warranty 1 Year

















