

Dynamic —

TD4 P PL TN

TD4 P PL BT

Pastry and bakery

28 - Pair of runners for grid EN 600x400 mm



Technical data	TD4 P PL TN	TD4 P PL BT
Gross volume	818 lt	818 lt
Working temperature	-2 / +8 °C	-15 / -22 °C
Motor type	Plug-in	Plug-in
Refrigerant	R290	R290
Refrigeration power	369 W (-10°C / +45°C)	568 W (-25°C / +45°C)
Absorption	263 W	616 W
Voltage/Frequency	230V/1-/50Hz	230V/1-/50Hz
Energy data (UE Reg. 2015/1094)		
Net Volume	538 lt	497 lt
Climate class	5 / (40°C - 40%)	5 / (40°C - 40%)
Type	This equipment is intended for use in ambient temperatures up to 40°C	
Refrigeration details		
Refrigeration unit	Tropicalized and easy extractable monoblock unit to guarantee reliability and performance at 43°C. Equipped with low consumption electronic fan motors	
Refrigerant charge	90 gr	95 gr
Evaporator	With cataphoresis anti-corrosion treatment	
Defrost	Automatic by hot gas for a shorter cycle and less thermal shock	
Condensate evaporation	Automatic through anti-corrosion treated compressor coil	

Construction details

	TD4 P PL TN	TD4 P PL BT
Product dimensions WxDxH	2500x800x900	2500x800x900
Packaging dimensions WxDxH	2550x850x1040	2550x850x1040
Gross weight	216 Kg	220 Kg
Worktop	Sturdy and resistant stainless steel AISI 304 worktop with rounded edges	
Structure	Stainless steel AISI 304 monocoque	
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel	
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)	
Inner corners	Rounded for an easy cleaning	
Door	4 Self-closing doors with 105° door stop, reversibles on site	
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption	
Feet	AISI 304 stainless steel, height adjustable (135mm-230mm)	

Functions


Control panel	High brightness touch screen display with 6 large digits. Tilted control panel
Functions	Three levels of ventilation intensity management, Led lighting ON/OFF, HACCP alarms through Ice connect (optional)
Connection	As optional: Remote access through serial interface. Via APP (only Android) it is possible to monitor HACCP traceability, appliance operation and parameters. Graphic and as CVS file export of registered data. Email sending of alarms notification

Accessories

Lighting	Optional
No. included accessories	28 - Pair of runners for grid EN 600x400 mm

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------



Heights with feet adjusted to H150 mm

Technical datasheet EN TD4 P PL TN / TB

Updated on 17 23-12-2023