

GH5000H



GH5000H



PORTABLE POWER

Technical

Model	GH 5000H – 'Hire Spec'
Type	Portable
Speed	3000 RPM
Phase/Voltage	1/240
Frequency	50 Hz
Max Output @ 0.8pf	5.0kVA

Noise Level (dBA @ 7m)	72
Frame	Extra Large roll frame

Engine

Manufacturer	Honda
Engine Model	GX390
Type	O.H.V.
Start	Recoil
Fuel	Unleaded Petrol
Run Time	3.0 hr @ 100%, 4.2hrs @60%
Tank Capacity	6.1 L
HP 3000 rpm cont	8.0 HP
Cubic Capacity	389 Cm ³
Oil Capacity	1.1 L

Alternator

Alternator Brand	Meccalte
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Outlets

Outlet	IP66 Rated 10amp + 15amp switched with Earth Leakage Circuit Breakers & RCD
---------------	---

Dimensions & Weight

Length	85 Cm
Width	57 Cm
Height	60 Cm
Weight	56 Kg

Options

Wheel kits	Two wheel or four wheel
Frames	Extra Large Roll Frames
Alternators	Oversized, Single or Three Phase
Long Range Tank	15 Litre Capacity
Start	Recoil or Electric Start

POWERED by
HONDA™

mecc alte spa