

The Leaders in Portable X-Ray Systems


Discovery III System

Top of the Line System in a Rugged Pelican Ca<mark>s</mark>e

- 12/15/22WN Detector options
- Wired & wireless operation modes
- 21.5" 1500 NIT Sun-Readable touch tablet
- MIL-DTL 38999 connectors
- Supports multi-tablet control & display
- Includes NOVO Touch Pro full Software package



NOVO Mesh Technology - Unmatched Wireless Performance







NOVO Wireless Mesh Technology

Unique technology providing unmatched wireless performance:

- High signal stability in crowded RF environments, such as urban locations and areas with strong electromagnetic fields
- Up to 0.6 miles (1000m) LOS between wireless devices; longer range when elevating on tripods - up to 1.8 miles (3km)
- Multiple wireless devices allow for working "around corners", obstacles and underground operations
- Each wireless unit becomes a relay (repeater), which automatically connects and automatically relays wireless signals efficiently





Components

NOVO 22WN Detector

- Internally shielded long life span
- High radiation resistance
- Low internal scattering higher image quality

Detector Imaging Area	Active Area	Detector Weight (Including Battery)	Detector Load Tolerance	Detector Drop Test
14.0" x 16.8" (35.6cm x 42.7cm)	85% Active Area	9.4 lbs. (4.3kg)	660 lbs. (300kg)	20" (50cm)
Detector Thickness	Bit Depth		Life Span	
0.6" (15.6mm)	16 bit latest generation		Over 100K rem*	

* Tested with Golden XRS-3 at ~ 10" (25cm)

Tablets (Most popular)







	NOVO Bright XL	NOVO Bright L	NOVO Bright S
Screen Size	21.5″	17"	10.1"
Screen Resolution	1920 x 1080	1920 x 1200	1920 x 1200
Screen Brightness (NIT)	1500 (!) Super Brightness	1500 (!) Super Brightness	1500 (!) Super Brightness
Touch Screen	\checkmark	\checkmark	\checkmark
Operating System	Windows 10	Windows 10	Windows 10
Battery Operation Time at 800 NIT	6+ hours	7+ hours	6+ hours

*Additional tablets and laptops supported